

Product Information

| | |
|---|---------------------------------------|
| Applicable products: | |
| Class Five™ toilet with Insuliner® insulated tank – left-hand trip lever | K-3656-U |
| Class Five™ toilet with Insuliner® insulated tank – right-hand trip lever | K-3656-UR |
| Fixture: | |
| Configuration | two-piece, elongated |
| Water per flush | 1.6 gal (6 L) |
| Passageway | 2-1/8" (5.4 cm) |
| Water area | 11-1/4" (28.6 cm) x 8-1/4" (21 cm) |
| Water depth from rim | 5-1/4" (13.3 cm) |
| Seat post hole centers | 5-1/2" (14 cm) |

| | |
|---|-----------|
| Included components: | |
| Tank cover | 1052368 |
| Tank cover locks | 1052368-T |
| Bowl, EB | K-4293 |
| Tank, Insulined, LH trip lever | K-4483-U |
| Tank, Insulined, RH trip lever | K-4483-UR |
| Tank, Insulined, LH trip lever, cover locks | K-4483-UT |
| Tank, Insulined, RH trip lever, cover locks | K-4483-RZ |

Installation Notes

Install this product according to the installation guide.

Fixture dimensions are nominal and conform to tolerances in ASME standard A112.19.2/CSA B45.1.

