

### Product Information

Applicable products:			
Toilet		K-3900	
Fixture:			
Configuration	one-piece, elongated		
Water per flush	1.28 gal (4.85 L) or .6 gal (2.5 L)		
Passageway	2-7/8" (73 mm)		
Water area	10" (254 mm) x 8-1/4" (210 mm)		
Water depth from rim	5-1/2" (140 mm)		
Included components:			
Inlet Hose Kit	1153579	Audio Cable	1142212
Remote Dock	1115508	FM Antenna	1142211
Dock to Toilet Cable	1115509	Installation Block Mounting Kit	1138879
Remote Control	1115507		

### Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Receptacle	120 VAC, 15 A minimum, 60 Hz

### Installation Notes

Install this product according to the installation guide.

Installation of a water hammer arrestor is recommended.

Install the docking station power cord and water hammer arrestor before installing the finished wall.

The supplied water inlet hose requires a supply stop with a 1/2" OD compression male outlet thread.

This model is fastened to the floor by mounting blocks. If local codes require the toilet be bolted to the flange, order flange installation kit 1171368 for required hardware and instructions.

Can be installed with water supply and electrical supply attached to the back wall or through the floor. See roughing-in illustration for details.

Adjust the through-the-floor installation as required to meet all local codes.

Fixture conforms to ASME Standard A112.19.2/CSA B45.1. All dimensions are nominal.

\*Through the Floor Installation Only.

