KOHLER Roughing-In

K-4920-T BRANHAM™ URINAL

Product Information

| Applicable product: | | | |
|---|-----------------|--------|--|
| 3/4" top spud stall urinal | K-4920-T | | |
| Fixture is ADA compliant. | | ADA | |
| Fixture: | | | |
| Configuration | Top spud | | |
| Water per flush | 1 gal* (3.78 L) | | |
| Spud inlet size | 3/4″ | | |
| * Designed to flush with one gallon (3.78 L) of water when installed with a water-saving flush valve. | | | |
| Recommended accessories: | | | |
| Strainer with china grate | | K-9172 | |
| Strainer with stainless steel beehive grate | | K-9183 | |

| Optional accessories: | | | |
|---|-------|---------|--|
| Seam cover [for urinal set on 21" (53.3 cm) centers] | | K-4931 | |
| Seam cover [for urinal set on 24" (61 cm) centers] | | K-4932 | |
| Touchless battery-powered urinal flush valve, fixture mounted | | K-13686 | |
| Included components: | | | |
| Spud | 18774 | | |
| Installation Notes | | | |

Installation Notes

Install this product according to the installation guide.

For proper drainage, install lip of urinal below floor level.

Refer to manufacturer's instructions and local codes for flush valve requirements.

Fixture conforms to ASME Standard A112.19.2/CSA B45.1. All dimensions are nominal.

