

KOHLER® Roughing-In

K-T45104, K-T45106, K-T45108 ALTEO™ RITE-TEMP® BATH AND SHOWER VALVE TRIM

Product Information

Applicable product:	
Bath and shower valve trim	K-T45104-4E
Shower valve trim, less diverter button	K-T45106-4E
Shower valve trim with diverter button	K-T45108-4E
Rite-Temp valve must be ordered to complete faucet.	

Required accessories:	
Rite-Temp® pressure-balancing valve OR	K-304-**
HiFlow Rite-Temp valve with stops OR	K-2971-**
Rite-Temp valve with push-button diverter	K-11748-**
** For a complete listing of all the Rite-Temp valves, refer to the individual valve Specification sheet or Roughing-in Sheet.	

Installation Notes

Install the valve trim according to the installation guide.

Install the Rite-Temp valve according to the installation guide.

NOTICE: Risk of product damage. Long screws, for installing trim, can damage the K-2971-KS valve. Consult the trim installation guide to verify if the thin wall installation kit (88526) is needed.

Avoid cross-flow conditions. Do not install a shut-off device on either valve outlet.

Cap the shower outlet if the deck-mounted spout, diverter, or handshower is connected to the spout outlet.

Install a 7" (178 mm) to 18" (457 mm) straight pipe or straight tube with single bath elbow between the valve and the wall-mount spout.

