

### Product Information

Applicable product:				
5.5' (1.7 m) BubbleMassage bath				K-809-G
Fixture*:				
Bathing well:				
Basin area, bottom		45" (114.3 cm) x 25" (63.5 cm)		
Basin area, top		58" (147.3 cm) x 29" (73.7 cm)		
Weight		510 lbs (231.3 kg)		
To overflow:				
Water depth		17-3/4" (45.1 cm)		
Capacity		97 gal (367.2 L)		
* Approximate measurements for comparison only.				
Drop-in cut-out		64-1/2" (163.8 cm) x 34-1/2" (87.6 cm)		
Cut-out for undermount		K-587 template		
Blower motor:	Heater	V	Hz	A
	300 W	220-240	50/60	3

### Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):

Blower motor/control	220-240 V, 15 A, 50/60 Hz
----------------------	---------------------------

### Installation Notes

Install this product according to the installation guide.

**NOTICE:** If the blower motor and check valve are **relocated**, two access panels are required. Locate one access panel at the blower motor/control location and the other at the control box. Locate the blower motor and check valve together.

Floor support under bath must provide for a minimum of 82 lbs/square foot (398 kg/square meter) loading.

Splitting the deck/surround is recommended if installing into a deck.

Hot water supply should be 70% of capacity or greater. Installations will vary.

Fixture conforms to ASME Standard A112.19.1/CSA B45.2. All dimensions are nominal.

