

KOHLER®

Roughing-In

K-1259-W1, K-1259-LW, K-1259-RW

MARIPOSA®

6' BATH WITH BASK™ HEATED SURFACE

Product Information

Applicable products:	
6' Drop-in bath with Bask heated surface	K-1259-W1
6' Bath with Bask heated surface – left drain (shown)	K-1259-LW
6' Bath with Bask heated surface – right drain	K-1259-RW

Fixture*:	
Bathing well:	
Basin area, bottom	50" (1270 mm) x 24" (610 mm)
Basin area, top	65" (1651 mm) x 27" (686 mm)
Weight	77 lbs (35 kg)
To overflow:	
Water depth	14" (356 mm)
Capacity	72 gal (272.5 L)
* Approximate measurements for comparison only.	

Heater:	W	V	HZ	A
	65	120	60	.5

Installation Notes

Install this product according to the installation guide.

Floor support under the bath must provide for a minimum of 39.1 lbs/square foot (190.7 kg/square meter) loading.

If used, the optional apron must be installed before the finished floor and wall materials are installed.

Locate a GFCI-protected 120 V, 15 A, grounded electrical outlet within 24" (610 mm) of the bath junction box.

40" (1016 mm) cable is included.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

