

### Product Information

|  |                                      |
|--|--------------------------------------|
| Applicable product:                      |                                      |
| Class Five toilet – left-hand trip lever | K-3989                               |
| Fixture:                                 |                                      |
| Configuration                            | Two-piece, elongated                 |
| Water per flush                          | 1.6 gpf (6 lpf) or 1.1 gpf (4.2 lpf) |
| Passageway                               | 2-1/8" (54 mm)                       |
| Water area                               | 11-3/8" (289 mm) x 8" (203 mm)       |
| Water depth from rim                     | 5-3/8" (137 mm)                      |
| Seat post hole centers                   | 5-1/2" (140 mm)                      |
| Included components:                     |                                      |
| Bowl                                     | K-4199                               |
| Tank                                     | K-4458                               |
| Tank cover                               | 1138565                              |
| Trip lever - Left hand                   | K-9237                               |
| Bolt cap accessory pack                  | 1013092                              |

Will comply with the American Disabilities Act (**ADA**) when installed per the requirements of the Accessibility Guidelines, Section 604 Water Closets, of the Act. The Model Plumbing Codes require the installation of elongated open-front toilet seats in public bathrooms.

Will comply with **CSA B651** when installed per Clause 4.3.6 of the standard.

Will comply with **OBC** when installed per Clause 3.8.3.8 and 3.8.3.9.

Fixture conforms to ASME Standard A112.19.2/CSA B45.1. All dimensions are nominal.

### Installation Notes

Install this product according to the installation guide.

