

### Product Information

Fixture: Approx. measurements for comparison only.	
Basin area, bottom	46" (1168 mm) x 24" (610 mm)
Basin area, top	54" (1372 mm) x 27" (686 mm)
Weight	73 lbs (33.1 kg)
Water depth	14" (356 mm) to overflow
Capacity	63 gal (238.5 L) to overflow

Amplifier/ control:	15 W (per channel)	120 V	50/60 Hz	-
Heater:	65 W	120 V	60 Hz	1.1 A

### Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD): 120 V, 15 A, 50/60 Hz

### Installation Notes

Install this product according to the installation guide. Ensure that the interface, amplifier, and transducers are functional before completing the installation.

Control amplifier fits 16" (406 mm) center studs. 25' (7.6 m) cables are included.

Locate the bath within 24" (610 mm) of a GFCI-protected 120 V, 15 A grounded electrical outlet. A second grounded outlet within the wall framing must be within 24" (610 mm) of the planned control amplifier. One electrical service may be used for the entire bath and related electrical components.

Drop-in cutout: 58" (1473 mm) x 34" (864 mm)

Floor support under bath must provide for a minimum of 41.6 lbs/square foot (203.1 kg/square meter) loading.

If installing a rim mount faucet, make sure any plumbing does not interfere with the drain overflow before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

The apron must be installed before the finished floor and wall materials are installed.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

