FLUSH MOUNT

PROJECT



DESCRIPTION

A looping radiant line casts light across space in a continuous helical path. The Synergy series is characterized by the rolled rectangular extrusion, which emits soft light through the silicon opal lens. Configured in both linear and ring arrangements, the arcing aluminum allows the curated finishes to be visible at every angle.







FM93820-AN Antique Brass

FM93820-AS Antique Silver


FM93820-BK Black




 $\ensuremath{^{\star}}$ For custom options, consult factory for details.

Fixture Dimensions	D20" x H6-5/8"
Light Source	LED
Wattage	32W
Total Lumens	2720lm
Delivered Lumens	AN-1625lm; AS-1842lm; BK-1236lm;
Voltage	120V
Color Temperature	3000K
CRI (Ra)	>90
Optional Color Temps	2700K - 5000K Available, Minimum Order Quantities Apply
LED Rated Life	50,000 hours
Dimming	100% - 10%, TRIAC or ELV Dimmer (Not Included)
Diffuser Details	Frosted acrylic diffuser
Location	Dry
Warranty	5 Years







K		7		\bigcap
\	\cup	_	\smile	<u> </u>

19054 28TH AVENUE SURREY - BC V3Z 6M3 CANADA COMMENT

c CINTED US
Intertek