LED Semi Flush

SF27716-3WCCT-UNV

INSTALLATION SHEET

START FROM HERE

- Make sure **POWER** is **COMPLETELY OFF** at the fuse box
- Have your fixture installed by a qualified licensed electrician
- Prepare everything in a clear area
- Wear gloves at all times during this installation
- · Read instructions carefully before you start assembly
- Keep this installation sheet for future reference

Technical Support: 1-855-855-8926

Please Note:

- This Kuzco LED fixture comes with pre-wired LED module(s)
- Unless instructed, Do Not touch any part of the LED module(s) as any unnecessary contact with the module could cause permanent damage
- Use ELV (Electronic Low Voltage) or TRIAC type of dimmer for dimming application
- 120-277V input

- **1.** Remove fixture from its original package
- **2.** Remove canopy cover **(3a)** from canopy **(2a)** by removing canopy screws **(2b)**
- **3.** Attach mounting plate **(1c)** to electrical junction box **(1a)** using junction box screws provided **(1e)** in hardware package
- Make proper electrical connections (black to hot "L", white to neutral "N", ground to "GND") with wire nuts (1b) provided in hardware package and place driver (4a) in canopy (2a)

- **5.** Choose color temperature by using slider (5a)
- **6.** Attach canopy cover (3a) to mounting plate (1c) with cover screws (3b)
- **1.** Attach canopy (2a) to canopy cover (3a) with canopy screws (2b)

