Kwikset UltraMax Security Knob Specifications

Kwikset L	IltraMax Security Knob Specifications			
Door Prep	Crossbore 2-1/8" Edge Bore 1" Latch Face 1" x 2-1/4" 2-3/8" standard. 2-3/4" optional. UL 2-3/4" standard. 2-3/8" optional.			
Backset				
Door Thickness	1-3/8"–1-3/4" doors standard. 2-1/4" doors optional on 720 and 740 models. 1-5/8" to 1-7/8" optional, 701 models.			
Cylinder	6-pin removable core. 5-pin optional.			
Faceplates	1" x 2-1/4" square corner standard. Round corner and other options available.			
Strikes	2-1/4" full lip square corner standard. Round corner and other options available.			
Bolt	1/2" throw. Nickel plated.			
Door Handing	Reversible for right- or left-handed doors.			
ANSI/BHMA	A156.2 Grade 2.			

Kwiks	et UltraMax	Security Knob Function Descriptions					
	720/725UL <i>F75</i>	Passage/Hall/Closet: Both knobs always free.					
	730/735UL <i>F76</i>	Privacy/Bed/Bath: Both knobs locked or unlocked by turnbutton inside. Outside knob unlocked by emergency key.					
	730 <i>F76</i>	Privacy/Bathroom: Same function as 730 above. Inside knob polished chrome.					
	740/745UL <i>F82</i>	Entry: Both knobs locked or unlocked by key outside or turnbutton inside.					
	741/746UL <i>F81</i>	Entry: Outside locked or unlocked by key outside or turnbutton inside. Inside always free.					
	744/749UL <i>F84</i>	Classroom: Outside locked or unlocked by key outside. Inside always free.					
	750/755UL <i>F86</i>	Storeroom/vestibule: Outside unlocked only while key is turned. Inside always free.					
	701	Store Door: Key in either knob locks or unlocks both knobs simultaneously. 1-3/8" standard. 1-5/8" to 1-7/8" optional.					
	788	Half Dummy Trim, Surface Mounted: For doors where only a pull is required. No operation.					

Note: ANSI functions are listed in italics.

Kwikset UltraMax Security Knob Dimensions							
Dimensions	Design	Α	В	C			
	Abbey	2-5/8"	2-3/4"	2-1/32"			
$B \longrightarrow$	Circa	2-5/8"	2-3/4"	2-1/8"			
	Cortez	2-5/8"	2-3/4"	2-1/8"			
Ä C	Hancock	2-5/8"	2-3/4"	2-3/8"			
	Laurel	2-5/8"	2-5/8"	2-7/16"			
<u>+</u> D	Roman	2-5/8"	2-3/8"	2-1/8"			

3	L03	5					
		อ	10B	15	15A	26	26D
•	•	•				•	•
•	•	•	•	•	•	•	•
•	•	•			•	•	•
•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	
		•					
	•	• •	• • •	• • • •	• • • • •	· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·



