

SPECIFICATION SHEET

WINE & BEVERAGE REFRIGERATOR

L3124UI1MSGLH - 24 Inch Single Zone Undercounter Wine & Beverage Refrigerator, Left Hinge - Stainless Steel

FEATURES

unwanted hotspots



ADDITIONAL FEATURES

- Temperature range: 34°F-65°F
- Includes two (2) full extension wine shelves, one (1) full extension beverage shelf, and one (1) shallow bottom shelf to fully utilize interior space
- The integrated door lock, along with the door ajar and temperature alarms, provide an extra layer of security
- Vibration-dampening wire shelves with stainless steel decorative fronts are both stylish and functional
- Zero-clearance door hinges allow for a seamless installation with adjacent cabinetry

WARRANTY

- Three (3) Years Parts and Labor
- Six (6) Years Sealed System Parts
- See Complete Warranty for Details





ACCESSORIES

Model	Description	Finish
HDLPRO	PRO Style Handle for Undercounter Models	Stainless Steel



Everglide™ System: A system of soft closing door hinges and shelves mitigates unwanted vibrations to your refrigerator's contents
 Fully height-adjustable shelves enable a user to move shelves up and down vertical tracking with the option to choose from a wide range of

• Best-in-class cabinet lighting runs the entire interior length of three sides

• Low-E, double-pane glass door with a layer of argon gas to maximize

heights, creating more or less space on each shelf

energy efficiency and deter harmful UV rays

with versatile LED color options: Blue, white and amber


Commercial grade 304 stainless steel interior and exterior cabinet

Precision cooling to drive air evenly throughout the interior, preventing




DIMENSIONS


FRONT



SIDE



TOP



SPECIFICATIONS

Model#	L3124UI1MSGLH
Capacity (750 mL Wine Bottles)	16
Capacity (12 oz. Cans)	70
Capacity (Volume)	5.2 cu ft
Product Depth	23-1/4"
Product Height (Min.)	34"
Product Width	23-13/16"
Product Weight	152 lbs
Refrigerant Type	R600a
Temperature Range	34°F–65°F
Power Cord Length	6'
Amps	1.5
Electric Supply	115 VAC, 60 Hz
	NEMA 5-15P

INSTALLATION NOTES

- The plug requires an additional 2" for clearance; a recessed receptacle may be required for fully recessed installations
- Dimensions in parentheses are in millimeters

CUTOUT DIMENSIONS

