



# LCN 3130 SERIES

## MOUNTING DETAILS

### CONCEALED MOUNTING

For interior doors.


Single acting cylinder and standard arm in top rail of door.

Concealed track in head frame.

### MAXIMUM OPENING

Templating allows 140°, trim permitting. 100° with optional bumper installed.

Adjustable hold-open points from 85° to 100°, with hold-open track.



- ▶ **Butt Hinges** should not exceed 5" (127 mm) in width.
- ▶ **Auxiliary Stop** is recommended at hold-open point or where a door cannot swing 140°. Optional track bumper assembly assists backcheck in cushioning the opening swing of the door. It is not intended to replace an auxiliary stop.
- ▶ **Top Rail** minimum 4" (102 mm) required.
- ▶ **Door Thickness** 1 3/4" (44 mm) minimum. Please consult the door manufacturer to assure that the door integrity and warranty is maintained after installing the 3130 Series door closer in a 1 3/4" thick wood door.
- ▶ **Door Width** 2'2" (660 mm) minimum.

### OPTIONS

- ▶ Standard track with Bumper
- ▶ Hold-open track
- ▶ Hold-open track with Bumper
- ▶ Consult factory for installations with pivots.


### SPECIAL TEMPLATES

Customized installation templates or products may be available to solve unusual applications. Contact LCN for assistance.

## CYLINDERS

### CYLINDER, 3130-3071


Standard, handed, cast iron cylinder assembly with mounting plate. For various applications see "Table of Sizes" on 3130 Series page 24.



## ARMS

### STANDARD ARM, 3130-3077T


Handed arm.  
Track roller not included with arm.



## TRACKS

### STANDARD TRACK, 3130-3038

Standard, non hold-open, non-handed track.  
Will accept hold-open clip and/or bumper assembly.



### STANDARD TRACK with BUMPER, 3130-3038B


Optional, non hold-open, non-handed track with bumper.  
Will accept hold-open clip.

### HOLD-OPEN TRACK, 3130-3038H

Optional, non-handed hold-open track.  
Will accept bumper assembly.

### HOLD-OPEN TRACK with BUMPER, 3130-3038HB


Optional, non-handed hold-open track with bumper.



## INSTALLATION ACCESSORIES

### TRACK BUMPER, 3130-169

Mounts in track to assist backcheck, does not replace auxiliary stop. Limits maximum opening.  
Consists of bumper, bumper post, and mounting screw.




### HOLD-OPEN CLIP, 3130-3054

Mounts in track to provide hold-open function.  
Hold-open point controlled by clip location.

### TRACK ROLLER, 3130-3034

Quiet, low friction roller assembly.  
Shoulder dimension "X" = 1/8" (2mm).




# LCN 3130 SERIES

**TABLE OF SIZES** Select closer based on width of door.  
 3130 Series cylinders available in size 1, 2, or 3.  
 Closing power of 3130 Series closers is not adjustable.

→ Indicates recommended range of door width for closer size.

**INTERIOR DOOR WIDTH**



3132  
3133

Minimum Door Width

## HOW-TO-ORDER 3130 SERIES CLOSERS

**1. SELECT CYLINDER SIZE**

- 3131 (ADA)
- 3132
- 3133

**2. SPECIFY HAND**

- RH
- LH

**3. SPECIFY FINISH**

- Standard Powder Coat \_\_\_\_\_  
 Aluminum, Dark Bronze, Tan, Statuary,  
 Light Bronze, Black, Brass.

**Closer will be shipped with:**

- STANDARD ARM,
- TRACK ROLLER,
- STANDARD TRACK,
- WOOD and MACHINE SCREW PACK,  
 unless options listed below are selected.

## CLOSER OPTIONS

**TRACK**

- Standard with Bumper (BUMPER)
- Hold-open (H)
- Hold-open with Bumper (HBUMPER)

**FINISHES**

- Custom Powder Coat (RAL) \_\_\_\_\_
- Plated Finish, US \_\_\_\_\_
- SRI primer

**SCREW PACK**

- TORX Machine Screw

**SPECIAL TEMPLATE**

- ST- \_\_\_\_\_

## REDUCED OPENING FORCE 3130 CLOSERS

**CAUTION !** Any manual door closer, including those certified by BHMA to conform to ANSI Standard A156.4, that is selected, installed and adjusted based on ADA or other reduced opening force requirements may not provide sufficient power to reliably close and latch a door.

Refer to POWER OPERATORS section for information on systems that meet reduced opening force requirements without affecting closing power.

|  | DOOR WIDTH | 36"  | 42"  | 48"  |
|--|------------|------|------|------|
|  | 8.5* lbs.  | N/A  | N/A  | N/A  |
|  | 5.0* lbs.  | 3131 | 3131 | 3132 |

\* Maximum opening force