



NEMA Configuration Table

NEMA Straight Blade Devices											
	15 AMPERE		20 AMPERE		30 AMPERE		50 AMPERE		60 AMPERE		
	RECEPT	PLUG	RECEPT	PLUG	RECEPT	PLUG	RECEPT	PLUG	RECEPT	PLUG	
2 Pole, 2 Wire Grounding	125V										
	250V										
	277VAC										
3 Pole, 3 Wire Non-Grounding	125/250V										
	125/250V										
3 Pole, 4 Wire Grounding	3.250V										
	3.120/208V										

IEC 309.1 & 309.2 Pin and Sleeve Devices																
	16/20 AMPERE				30/32 AMPERE				60/63 AMPERE				100/125 AMPERE			
	RECEPT	PLUG	CONN	BACKBOX	RECEPT	PLUG	CONN	BACKBOX	RECEPT	PLUG	CONN	BACKBOX	RECEPT	PLUG	CONN	BACKBOX
2 Pole 3 Wire	125V															
	100/130V															
	277V															
3 Pole 4 Wire	250V															
	200/250V															
	480V															
4 Pole 5 Wire	380/415V															
	125/250V															
	302/77/480V															

NEMA Turnlok® Devices

	15 AMPERE		20 AMPERE		30 AMPERE	
	RECEPT	PLUG	RECEPT	PLUG	RECEPT	PLUG
2 Pole, 2 Wire Non-Grounding	125V					
	250V					
	125V					
2 Pole, 3 Wire Grounding	250V					
	277V					
	480V					
3 Pole, 3 Wire Non-Grounding	600V					
	347V					
	125/250V					
3 Pole, 4 Wire Non-Grounding	3ø250V					
	3ø480V					
	3ø600V					
3 Pole, 4 Wire Grounding	125/250V					
	3ø250V					
	3ø600V					
4 Pole, 4 Wire Non-Grounding	120/208V					
	3øY 277/480V					
	3øY 347/600V					
4 Pole, 5 Wire Grounding	120/208V					
	3øY 277/480V					
	3øY 347/600V					

50 Amp Locking Devices

	RECEPT	PLUG	
2 Pole, 3 Wire Grounding			125V CORROSION RESISTANT
			125V CALIFORNIA STANDARD
			250V CALIFORNIA STANDARD
3 Pole, 4 Wire Grounding			480V CALIFORNIA STANDARD
			600VAC/ 250VDC CORROSION RESISTANT
			125/250V CORROSION RESISTANT
3 Pole, 4 Wire Grounding			125/250V CALIFORNIA STANDARD
			3ø250V CALIFORNIA STANDARD
			3ø480V CALIFORNIA STANDARD
3 Pole, 4 Wire Grounding			600VAC/ 250VDC CORROSION RESISTANT
			600VAC/ 250VDC CORROSION RESISTANT
			600VAC/ 250VDC CORROSION RESISTANT

Angle Adapters

	15 AMPERE	20 AMPERE	30 AMPERE	
EHU15AN				Straight Blade EHU, 3 Wire
L15-AN				Turnlok, 3 Wire
L203045-AN				Turnlok, 4 & 5 Wire

Key

SR	Single Receptacle		Open Slots Indicate receptacle configurations (female).
DR	Duplex Receptacle		Closed Slots Indicate plug blade configurations (male).
C	Connector		
P	Plug		
AN	Angle Plug		
AP	Angle Adapter		
FI	Flanged Inlet		
FO	Flanged Outlet		
X, Y, Z	Hot Lead		
W	Neutral Lead		
G	Grounding Lead		

