

Job Name/Location:

Tag No.:

Date:

| | | |
|------|----------|------------|
| For: | File | Resubmit |
| | Approval | Other_____ |

PO No.:

Architect: GC:

Engr: Mech:

Rep: (Company) (Project Manager)

KSSAP361A
R32 Single-Zone Extended Piping Wall Mount
 Outdoor Unit (ODU) - KUSAP361A, Indoor Unit (IDU) - KNSAP361A



Performance:

Cooling:

| | |
|--|---------------------|
| Cooling Capacity (Min~Rated~Max) (Btu/h) | 3,070~33,000~34,000 |
| SEER2 | 20.0 |
| EER2 | 10 |

SEER - Seasonal Energy Efficiency Ratio EER - Energy Efficiency Ratio

Heating:

| | |
|--|---------------------|
| Heating Capacity (Min~Rated~Max) (Btu/h) | 3,070~35,200~38,900 |
| HSPF2 | 8.5 |
| Max. Heating @ Indoor 70°F DB | |
| Outdoor 19°F DB / 17°F WB | 30,000 (85%) |
| Outdoor 6°F DB / 5°F WB | 26,000 (74%) |
| Outdoor 1°F DB / 0°F WB | 23,210 (66%) |
| Outdoor -3°F DB / -4°F WB | 21,620 (61%) |

HSPF - Heating Seasonal Performance Factor
 Cooling Nominal Test Conditions: Indoor: 80°F DB / 67°F WB Outdoor: 95°F DB / 75°F WB
 Heating Nominal Test Conditions: Indoor: 70°F DB / 60°F WB Outdoor: 47°F DB / 43°F WB

Electrical:

| | |
|---|-------------------|
| Power Supply (V/Hz/Ø) | 208-230/60/1 |
| MOP (A) | 30.0 |
| MCA (A) | 23.0 |
| Cooling Rated Amps (A) | 15.00 |
| Heating Rated Amps (A) | 13.20 |
| Compressor (A) | 15.1 |
| Fan Motor (IDU + ODU) (A) | 0.5 + 0.4 |
| Cooling Power Input (kW) (Min~Rated~Max @95°F) (kW) | 0.500~3.300~4.020 |
| Heating Power Input (kW) (Min~Rated~Max @47°F) (kW) | 0.660~2.933~4.370 |

MOP - Maximum Overcurrent Protection MCA - Minimum Circuit Ampacity

Piping:

| | |
|--|-------------|
| Liquid Line (in., O.D.) | 3/8 Flare |
| Vapor Line (in., O.D.) | 5/8 Flare |
| Additional Refrigerant (oz./ft.) | 0.32 |
| Min. / Max. Pipe Length (ft.) ² | 9.8 / 164.0 |
| Piping Length (no add'l refrig., ft.) | 24.6 |
| Max. Elevation (ft.) | 98.4 |

Features:

- 24-Hour On / Off Timer
- 4-Way Auto Swing
- Auto Restart / Auto Changeover
- Jet Cool / Jet Heat
- Inverter (Variable Speed Compressor)
- Smart Diagnosis
- Washable Filter
- Self-Cleaning Indoor Coil
- Built-in Base Pan Heater
- Built-in Wi-Fi via Smart ThinQ app
- Low ambient cooling down to 14°F (0°F with Wind Baffle Kit)

Included Accessories:

- Wireless Remote Controller — AKB76044208

Optional Accessories:

- Low Ambient Wind Baffle (Cooling operation to 0°F) - ZLABGP04B

Controller Options:

- MultiSITE™ CRC* Controllers
 - Standard III Remote Controllers
 - Dry Contacts
 - PI-485
 - AC Smart 5 Central Controller
 - MultiSITE Communication Mgr.
 - LonWorks® Gateway
 - ACP 5 BACnet® Gateway
- BACnet® is a registered trademark of ASHRAE. LonWorks is a registered trademark of Echelon Corp.

Operating Range:

Outdoor Unit:

| | |
|-----------------|----------|
| Cooling (°F DB) | 14 ~ 118 |
| Heating (°F WB) | -4 ~ +65 |

Indoor Unit:

| | |
|-----------------|---------|
| Cooling (°F WB) | 53 ~ 75 |
| Heating (°F DB) | 60 ~ 86 |

System Data:

| | |
|--|-------------------|
| Refrigerant Type | R32 |
| Refrigerant Control | EEV |
| Refrigerant Charge (lbs.) | 4.406 |
| ODU Sound Pressure (Cooling / Heating) (±1 dB[A]) ³ | 55 / 58 |
| IDU Sound Pressure | |
| Cooling (H/M/L/Sleep) (±1 dB[A]) ³ | 51 / 47 / 43 / 33 |
| Heating (H/M/L) (±1 dB[A]) ³ | 51 / 47 / 43 |
| ODU Net / Shipping Weight (lbs.) | 147.9 / 160.3 |
| IDU Net / Shipping Weight (lbs.) | 40.8 / 48.9 |
| Heat Exchanger Coating | GoldFin™ |

Fan:

| | |
|------------------------------|---------------------------------------|
| ODU Type | Propeller |
| IDU Type | Cross Flow |
| Fan Speeds (Fan/Cool/Heat) | 6 / 6 / 6 |
| Quantity (ODU + IDU) | 1 + 1 |
| Motor/Drive | Brushless Digitally Controlled/Direct |
| ODU Max. Air Flow Rate (CFM) | 2295 |
| IDU Air Flow | |
| Cooling, Max/H/M/L (CFM) | 1,095 / 883 / 742 / 601 |
| Heating, Max/H/M/L (CFM) | 1,166 / 954 / 813 / 671 |
| Dehumidification (pts./hr.) | 5.49 |

Notes:

1. Acceptable operating voltage: 187V-253V.
2. Piping lengths are equivalent.
3. Sound Pressure levels are tested in an anechoic chamber under ISO Standard 3745.
4. All communication / connection (power) cable from the outdoor unit to the indoor unit is field supplied and must be a minimum of four-conductor, 14 AWG, stranded, shielded or unshielded (if shielded, it must be grounded to the chassis of the outdoor unit only), and must comply with applicable local and national codes.
5. See Engineering Manual for sensible and latent capacities.
6. Power wiring cable size must comply with the applicable local and national code.
7. The indoor unit comes with a dry helium charge.
8. This data is rated 0 ft. above sea level, with 24.6 ft. of refrigerant line and a 0 ft. level difference between outdoor and indoor units.
9. Must follow installation instructions in the applicable LG installation manual.



For a complete list of available accessories, contact your LG representative.
 For continual product development, LG reserves the right to change specifications without notice.
 © LG Electronics U.S.A., Inc., Englewood Cliffs, NJ. All rights reserved. "LG Life's Good" is a registered trademark of LG Corp. /www.lghvac.com

KSSAP361A
R32 Single-Zone Extended Piping Wall Mount
 Outdoor Unit (ODU) - KUSAP361A, Indoor Unit (IDU) - KNSAP361A



Tag No.: _____

Date: _____

PO No.: _____



