

# FEATURES & SPECIFICATIONS

### INTENDED USE

Provides general illumination in residential and light commercial applications. Ideal for use in workshops, utility rooms and garages.

### **ATTRIBUTES**

Slim, compact design available in 1- or 2- lamp configurations. Quality, post-painted steel construction.

Includes 3000K linear T5 fluorescent lamps.


Normal power factor residential ballast (120 volt, 60 Hz) ensures no flickering and quiet operation. For use with non-dimmable switches only.

#### LISTING

CUL listed to US and Canadian safety standards and suitable for damp locations.

### WARRANTY


Guaranteed for two years against mechanical defects.



**Indoor General Purpose** 

# **T5 Mini-Strip**


**Strip Light** 



### **DIMENSIONS**


Nominal Size	Lamp Configuration	Model Number	Number of Lamps	(A) Width inches (cm)	(B) Length inches (cm)	(C) Height inches (cm)
2'		MNS5 1 14 LP	(1) 14W Linear T5	1-1/2" (3.5)	22-3/4" (57.8)	2-1/8" (5.2)
2'		MNS5 2 14 LP	(2) 14W Linear T5	1-3/4" (2.8)	22-3/4" (57.8)	2-3/8" (5.8)
3'		MNS5 1 21 LP	(1) 21W Linear T5	1-1/2" (3.5)	34-3/4" (86.8)	2-1/8" (5.2)
3'		MNS5 2 21 LP	(2) 21W Linear T5	1-3/4" (2.8)	34-3/4" (86.8)	2-3/8" (5.8)
4'		MNS5 1 28 LP	(1) 28W Linear T5	1-1/2" (3.5)	46-3/4" (116.8)	2-1/8" (5.2)
4'		MNS5 2 28 LP	(2) 28W Linear T5	1-3/4" (2.8)	46-3/4" (116.8)	2-3/8" (5.8)

All dimensions are in inches (centimeters)



# ORDERING INFORMATION

Choose the boldface catalog nomenclature that best suits your needs and write it on the appropriate line. Order accessories and replacement parts as separate catalog numbers.



Ballast/Voltage

(blank) 120 volt residential electronic ballast (standard)

Accessories/Replacement parts

DMNS514

DMNS514

DMNS521

3' white acrylic diffuser for MNS5 1 21

DMNS528

4' white acrylic diffuser for MNS5 1 28

Notes:

1. Lamps included.

Use with non-dimmable switches only
 Can be wall or ceiling mounted.

Example: MNS5 1 14

# Strip Light General Purpose

# **PHOTOMETRICS**

Full photometric data report available within 2 weeks from request. Consult factory.

