

FEATURES & SPECIFICATIONS

INTENDED USE

Provides general illumination in residential and light commercial applications. Ideal for use in workshops, utility rooms and garages.

Slim, compact design available in 1- or 2- lamp configurations. Quality, postpainted steel construction.

Includes 3000K linear T8 fluorescent lamps.

Normal power factor residential ballast (120 volt, 60 Hz) ensures no flickering and quiet operation. For use with non-dimmable switches only.

CUL listed to US and Canadian safety standards and suitable for damp locations.

WARRANTY


Guaranteed for two years against mechanical defects.

Catalog Number	
Notes	Туре

Indoor General Purpose


T8 Mini-Strip

Strip Light



DIMENSIONS


-	Nominal Size	Lamp Configuration	Model Number	Number of Lamps	(A) Width inches (cm)	(B) Length inches (cm)	(C) Height inches (cm)
	1011		145100 4 451 D	(4) 451411: TO	4 5 (01) (4 4)	10.0(0) (10.0)	0.0(4 .(0.0)
1	18"		MNS8 1 15 LP	(1) 15W Linear T8	1-5/8" (4.1)	18-3/8" (46.6)	2-3/4" (6.9)
1	18"		MNS8 2 15 LP	(2) 15W Linear T8	2-3/8" (6.0)	18-3/8" (46.6)	2-7/8" (7.3)
2	2'		MNS8 1 17 LP	(1) 17W Linear T8	1-5/8" (4.1)	24-3/8" (61.9)	2-3/4" (6.9)
2	2'		MNS8 2 17 LP	(2) 17W Linear T8	2-3/8" (6.0)	24-3/8" (61.9)	2-7/8" (7.3)
3	3'		MNS8 1 25 LP	(1) 25W Linear T8	1-5/8" (4.1)	36-3/8" (92.3)	2-3/4" (6.9)
3	3'		MNS8 2 25 LP	(2) 25W Linear T8	2-3/8" (6.0)	36-3/8" (92.3)	2-7/8" (7.3)
2	1'		MNS8 1 32 LP	(1) 32W Linear T8	1-5/8" (4.1)	48-3/8" (122.9)	2-3/4" (6.9)
	1'		MNS8 2 32 LP	(2) 32W Linear T8	2-3/8" (6.0)	48-3/8" (122.9)	2-7/8" (7.3)




All dimensions are in inches (centimeters)

ORDERING INFORMATION

Choose the boldface catalog nomenclature that best suits your needs and write it on the appropriate line. Order accessories and replacement parts as separate catalog numbers.



Accessories/Replacement parts
18" white acrylic diffuser for MNS8 1 15 LP
2' white acrylic diffuser for MNS8 1 17 LP
3' white acrylic diffuser for MNS8 1 25 LP
4' white acrylic diffuser for MNS8 1 32 LP



(blank) 120 volt residential electronic ballast (standard)

Lamps included.
Use with non-dimmable switches only.
Can be wall or ceiling mounted.

Example: MNS8 1 15

DMNS815 **DMNS817**

DMNS825 DMNS832

T8 Mini-Strip Light General Purpose

PHOTOMETRICS

Full photometric data report available within 2 weeks from request. Consult factory.



Consumer Products