

Catalog Number
Notes
Type

FEATURES & SPECIFICATIONS

INTENDED USE — The CPX Series LED is a low-glare luminaire featuring an external driver. This cost-effective, reliable luminaire is visually comfortable and can be recessed mounted. Suitable for many applications such as schools, offices, retail, convenience stores, and other commercial spaces. Certain airborne contaminants can diminish integrity of acrylic. [Click here for Acrylic Environmental Compatibility table for suitable uses](#). Adjustable Lumen (AL07, AL08) and Switchable White (SWW7) configurations available. **U.S. Patent No. 10,681,784.**

CONSTRUCTION — The extruded aluminum frame with satin white lens provides excellent shielding and uniform luminance. CPX's low-profile design provides increased installation flexibility especially in restricted plenum spaces. The back plate includes integral T-bar clips for installation into T-grid ceilings.

ELECTRICAL — Long-life LEDs, coupled with a high-efficiency driver, provide superior illumination for extended service life. Greater than 70% LED lumen maintenance at 50,000 hours (L70>50,000).

LISTINGS — Pending Certification. Damp location listed. IC rated.

WARRANTY — 5-year limited warranty. Complete warranty terms located at: www.acuitybrands.com/support/customer-support/terms-and-conditions


Note: Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25 °C.

Specifications subject to change without notice

CPX LED

Luminaire



ORDERING INFORMATION

Catalog Number	UPC	Description	Lumens	Color Temperature	CRI	Voltage	Wattage	Efficacy	Pallet Qty.
CPX 2X4 40L 40K 120 NODIM CP2	194994450481	2x2 LED Luminaire	4000	4000K	80	120	40		20

DIMENSIONS

Length: 47.8" 121.4cm
 Width: 23.8" 60.5cm
 Depth: 1.7" 4.3cm
 Weight:
 Unit: 22.04lbs
 Unit Carton: 27.78lbs

