



Catalog Number
Notes
Type

Contractor Select™
OSC LED
 LED Wall Pack

The OSC LED Residential Entry Light Wall Pack provides flexibility for on-site customization with switchable color temperature (3000K/4000K/5000K), a selectable photocell and multiple lens options. This versatile lighting solution is ideal for residential outdoor applications such as doorways, entryways, patios, and other outdoor spaces where dependable and efficient lighting is essential.

FEATURES:

- Three diffuser options included (long diffuser, short diffuser, no diffuser)
- Switchable CCT - 30/40/50K
- Selectable photocell for dusk-to-dawn or switched operation



Catalog Number	UPC	Description	Lumens	Input Watts	CCT	CRI	Voltage	Dusk-to-Dawn Operation	Finish
OSC LED SWW2 120 PE DDB M4	00197589211184	OSC LED Entry Light	800	9.5	3000/4000/5000K	80	120	Included Standard, Selectable On*/Off	Dark Bronze



Specifications

INTENDED USE:

The OSC LED provides years of maintenance free general illumination for residential and light commercial outdoor applications such as doorways, patios, loading areas and warehouses.

CONSTRUCTION:

Rugged cast-aluminum, corrosion-resistant housing with three impact resistant Polycarbonate lens options (long lens, short lens, or no lens) to soften illumination and resist fading and cracking. 120V driver operates at 60Hz. Rated for outdoor installations, 40° C maximum ambient.

OPTICS:

High performance LEDs produce over 800 lumens and maintain 70% of light output at 50,000 hours of service. An integrated photocell turns light on at dusk and off at dawn for additional energy savings and added convenience. See Lighting Facts label for specific fixture performance.

INSTALLATION:

Mounts easily to existing junction box on wall.

LISTINGS:

UL Listed to U.S. and Canadian safety standards for wet locations. Tested in accordance with IESNA LM 79 and LM 80 standards.

WARRANTY:

5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

Dimensions

Specifications

Width: 4.35" (11.1 cm)

Height 1: 5.39" (13.7 cm)

Height 2: 3.3" (8.4 cm)

Height 3: 4.96" (12.6 cm)

Depth: 4.90" (12.4 cm)

Weight: 1.03 lbs (0.47 kg)

