

FEATURES & SPECIFICATIONS

INTENDED USE

Provides general illumination in residential and light commercial applications. Ideal for use in foyers, hallways, bedrooms, offices, utility work areas, stairways and many other rooms in the house.

ATTRIBUTES

Arts and crafts styling. Offered in either an antique bronze finish with sandtextured beige glass diffuser or a brushed-nickel finish with a sand-textured opal glass diffuser. Diffuser provides a wide spread uniform illumination.

Includes (1) 40W, (1)55W 2C T6 3500K fluorescent lamp for energy efficiency, superior color rendering and long life.

Standard with electronic ballast (120 volt, 60Hz) ensures no flickering and quiet operation without interfering with other home electronics.

For use with non-dimmable switches only.

All mounting hardware included.

tions. ENERGY STAR® qualified.

Catalog Number Notes Tvpe

Indoor Decorative

Piedmount Flush Mount

CLASSIC COLLECTION

2C T6 Fluorescent






CUL listed to US and Canadian safety standards and suitable for damp loca-Guaranteed for two years against mechanical defects in manufacture.


DIMENSIONS

Nominal Size	Lamp Configuration	Model Number	Number of Lamps	(A) Width inches (cm)	(B) Length inches (cm)	(C) Depth inches (cm)
16-1/4" dia.		10866	(1) 40W 2C T6	16-1/4" (41.3)	16-1/4" (41.3)	6-1/4" (15.9)
18-1/2" dia.		10867	(1) 55W 2C T6	18-1/2" (47.0)	18-1/2" (47.0)	7" (17.8)

^{*} Maximum extension from ceiling

All dimensions are in inches (centimeters)





ORDERING INFORMATION

Choose the boldface catalog nomenclature that best suits your needs and write it on the appropriate line. Order accessories as separate catalog numbers.

Model Number ^{1,2,3}							
10866	16-1/4" diameter - (1) 40W 2C T6 2700K fluores-						
	cent lamp Included						

10867 18-1/2" diameter - (1) 55W 2C T6 2700K fluores-

cent lamp Included

Finish							
BZA	Antique bronze						
BN	Brushed nickel						

Ballast/Voltage² 120 volt residential electronic (blank) ballast (standard)

Options (Consult factory)

Example: 10866 BZA

Other voltage and ballast types (Consult factory)

Accessories/Replacement parts

F2C4027 R6 F2C5527 R6 **DPIED14FMCS DPIED16FMCS DPIED14FMWS DPIED16FMWS** 40W 2C T6 2700K fluorescent lamp4 55W 2C T6 2700K fluorescent lamp4 Sand-textured diffuser, beige 19" Sand-textured diffuser, beige Sand-textured diffuser, opal 16" 19" Sand-textured diffuser, opal

- Oues:

 "INCLUDES (1) 40W or (1) 55W 2C T6 3500K fluorescent.

 Use with non-dimmable switches only.

 Resale packs must be considered in increments of 6.

Piedmount Flush Mount

PHOTOMETRICS

Full photometric data report available within 2 weeks from request. Consult factory.

