

Catalog Number	
Notes	Туре

Outdoor General Purpose

FEATURES & SPECIFICATIONS

INTENDED USE

Provides general illumination for outdoor use in residential and light commercial applications. Ideal for entryways, walkways, side yards, patios, and commercial buildings creating an inviting exterior space as well as providing safety and security.

ATTRIBUTES

Dusk-to-dawn photocell automatically turns on at dusk and off at dawn for convenience and energy savings. The durable polycarbonate housing is offered in bronze or white. High-impact polycarbonate refractor is UV-stablized to prevent yellowing.

Standard with electronic ballast (120 volt, 60 Hz). Starts instantly down to -13°F (-26°C)

Includes (1) 42W GX24q 4-pin base 4100K triple tube compact fluorescent

For use with non-dimmable switches only.

All mounting hardware included.


LISTING

CUL listed to US and Canadian safety standards and suitable for wet locations. ENERGY ${\sf STAR}^{\circledcirc}$ qualified.

WARRANTY

Guaranteed for two years against mechanical defects in manufacture. (Excludes lamp)

Mini-Wall Pack Dusk-to-Dawn



Compact Fluorescent






DIMENSIONS

Lamp Configuration	Model Number	Number of Lamps	(A) Width inches (cm)	(B) Height inches (cm)	(C) Extension* inches (cm)
	OWP3 42F	(1) 42W GX24q 4-pin base compact (TTT)	5-3/4" (14.6)	11" (27.9)	4-15/16" (10.9)

^{*} Maxium extension from wall


All dimensions are in inches (centimeters)




Example: OWP3 42F 120 P LP BZ

ORDERING INFORMATION

Choose the boldface catalog nomenclature that best suits your needs and write it on the appropriate line. Order accessories as and replacement parts separate catalog numbers.



tube compact fluorscent lamp



120 volt residential electron ballast (standard)



P Dusk-to-Dawn photocell



LP Lamp included



BZ Bronze WH White

Accessories/Replacement parts

CF42TRT41 4-PIN M6 42W GX24q 4-pin 4100K triple tube compact fluorescent lamp

Outdoor General Purpose

P	Н	ΠT	'n	M	F1	ΓR	ICS

Full photometric data report available within 2 weeks from request. Consult factory.



DMWP.pmd

Rev. 07/09