

Catalog Number
Notes
Type

FEATURES & SPECIFICATIONS

INTENDED USE — Provides general illumination for residential and commercial applications. Ideal for use as lighting in bathroom/lavatories, over hospital beds, hallways/corridors, stairways and utility areas.

CONSTRUCTION — Fashionable look that matches any décor. White end caps available in 1 and 2 lamp configurations. Durable milk-white acrylic diffuser provides a widespread uniform illumination. Suitable for vertical or horizontal mounting. Available in 2', 3' and 4' lengths.

For use with non-dimmable switches only.

OPTICS — Utilizes linear T8 fluorescent lamps for energy efficiency, superior color rendering and long life (not included).

Standard with electronic ballast (120 volt, 60Hz) ensures no flickering and quiet operation without interfering with other electronics. Also available in other ballast configurations.


LISTINGS — CUL listed to US and Canadian safety standard on Residential Electronic (RE) ballast fixtures and suitable for damp locations. For Non-RE ballast, UL and CSA (standard) for NOM Certified see options.

WARRANTY — Guaranteed for two years against mechanical defects in manufacture.

Note: Specifications subject to change without notice.

Indoor Decorative

Contemporary Vanity




Linear T8 Fluorescent



DIMENSIONS						
Nominal size	Lamp configuration	Model number	Number of lamps	(A) Width inches (cm)	(B) Length inches (cm)	(C) Depth* inches (cm)
2'		11852	(2) 17W linear T8	4-5/8 (11.7)	24 (61.0)	4-1/2 (11.4)
		11872	(1) 17W linear T8	4-5/8 (11.7)	24 (61.0)	4-1/2 (11.4)
3'		11853	(2) 25W linear T8	4-5/8 (11.7)	36 (91.4)	4-1/2 (11.4)
		11873	(1) 25W linear T8	4-5/8 (11.7)	36 (91.4)	4-1/2 (11.4)
4'		11854	(2) 32W linear T8	4-5/8 (11.7)	48 (121.9)	4-1/2 (11.4)
		11874	(1) 32W linear T8	4-5/8 (11.7)	48 (121.9)	4-1/2 (11.4)

*Extension from ceiling.
All dimensions are inches (centimeters) unless otherwise indicated.



ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Example: 11852RE

Model number ^{1,2}	Residential ballast ³	Ballast/Voltage ⁴	Options
<u>2' fixture</u> 11852RE White - (2) 17W linear T8 fluorescent lamp required 11872RE White - (1) 17W linear T8 fluorescent lamp required	RE 120 volt residential electronic ballast (standard) (blank) Other voltage and ballast types available (see ballast/voltage)	(blank) RE ballast fixtures only MVOLT Multi-volt 120 120 volt 277 277 volt 347 347 volt Other voltage and ballast types (consult factory)	GEB Electronic ballast, <20%THD GEB10IS T8 electronic ballast, <10%THD, instant start GEB10RS T8 electronic ballast, 10% THD, rapid start NOM NOM Certified (Consult factory for other options)
<u>3' fixture</u> 11853RE White - (2) 25W linear T8 fluorescent lamp required 11873RE White - (1) 25W linear T8 fluorescent lamp required			
<u>4' fixture</u> 11854RE White - (2) 32W linear T8 fluorescent lamp required 11874RE White - (1) 32W linear T8 fluorescent lamp required			

Accessories: Order as separate catalog number.	
DWC24	White acrylic diffuser 2'
DWC36	White acrylic diffuser 3'
DWC48	White acrylic diffuser 4'

Notes

- Lamps not included.
- Use with non-dimmable switches only.
- Residential electronic ballast standard and requires RE designation.
- No designation for lamp type is required on RE ballast fixtures.

PHOTOMETRICS

Full photometric data report available within 2 weeks from request. Consult factory.