

FEATURES & SPECIFICATIONS

INTENDED USE

Provides accent illumination in residential and light commercial applications. Ideal for use as toe-kick lighting for counter cabinets providing a warm inviting atmosphere in the kitchen. Also use in bookcases and display cabinets.

Long-lasting LEDs - 40,000 hours average bulb life. 1/2" low-profile light sticks, available in 6", 12" and 18" lengths. Quick-connect brackets or double sided tape allows for guick and easy installation. Light sticks can be linked end-toend for continuous illumination. 3" linking cord accessory links fixtures around corners, or for wider spacing use 24" linking cord accessory (order separately - see accessories).

Includes .1 watt LED bulbs, for a bright illumination and long life. Total wattage 0.45W 6"stick, 0.9W 12'stick and 1.35W for 18" stick.


Requires 24V step down transformer kit (sold separately - see accessories below). Links up to 10' of fixtures on one transformer. Kit includes 6' power cord and 24" transformer linking cord. Can be direct-wired with splice box and 24" connector cord, (order separately - see accessories below).

26" cord with In-line power switch available (order separately - see accessories below).

All mounting hardware included.

CUL listed to US and Canadian safety standards and suitable for damp locations.

Guaranteed for two years against mechanical defects in manufacture.




Indoor General Purpose

Cabinet Light

Linkable Stick - LED






DIMENSIONS

Nominal Size	Model Number	Number of Lamps	(A) Width inches (cm)	(B) Length inches (cm)	(C) Extension* inches (cm)
6"	STK6	0.45W 24V LED	1/2" (1.3)	6-1/4" (10.5)	3/8" (1.0)
12"	STK12	0.9W 24V LED	1/2" (1.3)	12-1/4" (31.1)	3/8" (1.0)
18"	STK18	1.35W 24V LED	1/2" (1.3)	18-1/4" (46.4)	3/8" (1.0)

^{*} Extension from ceiling



ORDERING INFORMATION

Choose the boldface catalog nomenclature that best suits your needs and write it on the $\underline{appropriate \ line. \ Order \ accessories \ and \ replacement \ parts \ as \ separate \ catalog \ numbers.}$

Model Number^{1,2}

6" - 0.45W 24-volt (6) integral LED bulbs Included 12" - 0.9W 24-volt (12) integral LED bulbs Included STK18 18" - 1.35W 24-volt (18) integral LED bulbs Included STKTRANS 24 24-volt transformer required*

> *Links up to 10' of fixtures per transformer. Includes 6' power cord and 24" transformer linking cord.

Accessories/Replacement parts				
INLS26	In-line power switch with 26" cord			
UCD JB R12	Splice box ² (for easy direct wiring - 24" cord connector required)			
UC ERC24 R12	24" cord connector ² (required when using splice box)			
UCH WWC R12	18" cord cover ² (conceal cords)			
STKCC24	24" LED connector cord (for longer spacing between fixures)			
CTKCC3	3" LED connector cord (for linking fixtures around corners)			

- Notes:
 1. INCLUDES 0.45W 24 volt LED ballasts, 0.9W 24 volt LED ballasts or 1.35W 24 volt LED ballasts.
- 2. Resale packs must be orderedin increments of 12.

Example: STK6 BZ

All dimensions are in inches (centimeters)

Stick General Purpose

PHOTOMETRICS

Full photometric data report available within 2 weeks from request. Consult factory.



Consumer Products

STGC.pmd