



1/2 hp sewage pump, 208-230V, 20' cord, 60HZ, 2" discharge, manual operation

Item: 511438

Model: 10SC-CIM

★★★★★ (0) Write a review

Ratings

HP	1/2 hp
Frequency	60 Hz
Phase	Single-Phase
Amps - Full Load	5.5 A
Amps - Starting	13 A
Full Load Watts	1214 W
Volts	208 VAC / 230 VAC
Cord Length	20 ft
Pump Power Cord Type	SJTW
Pump Power Cord Gauge	18-3
Motor Type	Submersible
Continuous Duty	Yes
Thermal Overload Protection	Yes
Maximum Flow Rate - 60Hz	120 gpm / 7200 gph
Minimum Flow Rate - 60Hz	5 gpm / 300 gph
Max Flow Rate - 50Hz	120 gpm / 7200 gph
Shut-Off	25 ft
Minimum Head - 60Hz	5 ft
Shut Off Height - 50Hz	25 ft
Shut Off Height - 60Hz	25 ft
Stages	1
Max Solid Handling Size	2"
Switch Type	Manual

Want to be the first to know about the latest in pumping solutions?

YES, SIGN ME UP!

Liquid

Max Fluid Temperature	140 °F
-----------------------	--------

Materials of Construction

Pump Base Material	Cast Iron
Pump Body Material	Cast Iron
Pump Volute Material	Cast Iron
Impeller Type	Vortex
Impeller Material	Nylon
Motor Shaft End - Material	Steel
Check Valve	No
Intake Screen Material	Cast Iron Epoxi
Fasteners Material	Stainless Steel
Top Bearing Material	Steel
Top Bearing Type	Ball
Bottom Bearing Type	Ball Bearing
Seal Material	Carbon/Ceramic, Nitrile
Seal Type	Mechanical Seal

Installation

Discharge Type	Threaded - FNPT
Discharge	2 "
Product Length	10.4 "
Product Width	8.6 "
Product Height	14 "
Pump Length	10.4 "
Product Weight	36.5 lb
Product Weight w/ Pack	37.5 lb
Carton Length	12.4 "
Carton Width	10.24 "
Carton Height	17.44 "

Other

Accessories Included	None
Electrical Agency Approvals	CSA
Standard Warranty	36 Months
	Warranty Terms Link

Want to be the first to know about the latest in pumping solutions?

Reviews



Review this Product

Questions

Be the first to ask a question

No questions have been asked about t



Be the first to review this product



**Want to be the first to know about
the latest in pumping solutions?**