


# Little GIANT®

## ES60 MODELS




### Features


- Powerful, 6/10 HP Permanent Split Capacitor (PSC) motor for high starting and running torque, with low amp draw to conserve electrical energy
- Two-vane, non-clog cast iron impeller with pump-out vanes to help protect seal; will pass 2" spherical solids
- Bearings: Upper and lower ball bearings for extended motor life
- Mechanical seal (stainless steel spring, nitrile parts, carbon and ceramic faces) to assure maximum protection against pump failure
- Rugged cast iron pump housing with epoxy coating for corrosion resistance
- 2" and 3" FNPT discharge flanges included
- Choice of automatic operation:
  - Diaphragm pressure switch
  - Wide angle float switch
- Oil-filled motor housing for lifetime bearing lubrication and maximum heat dissipation
- Stainless steel hardware to protect against corrosion
- Thermal overload protection



The new ES60 models are energy-saving, high performance, fully submersible sewage/effluent/high-capacity sump pumps, designed for the professional plumbing contractor. The powerful 6/10 HP PSC motor delivers 127 GPM @ 10' TDH, while drawing only 10.3 amps @ 115VAC, conserving electrical energy. The ES60 models are designed, manufactured and tested in accordance with Little Giant's demanding standards, and are backed by Little Giant's premier customer service.




# ES60 MODELS



## Specifications

Submersible Sewage Pumps

Model	Item	Listing	HP	Volts/ Hz	Discharge (FNPT)	Solids Handling	Running Amps					Shut Off	PSI	Cord Length	Weight	Dimensions (Inches)			
							5'	10'	15'	20'	25'					H	L	W	
ES60M1-10	511462	cCSAus	6/10	115/60	2" (3" Flanged Discharge Included)	2"	10.3	155	127	98	70	29	28	12.1	10	61	14.8	12.25	10.8
ES60M1-20	511463	cCSAus	6/10	115/60	2" (3" Flanged Discharge Included)	2"	10.3	155	127	98	70	29	28	12.1	20	62	14.8	12.25	10.8
ES60M2-20	511482	cCSAus	6/10	230/60	2" (3" Flanged Discharge Included)	2"	5.2	155	127	98	70	29	28	12.1	20	62	14.8	12.25	10.8
ES60W1-10	511542	cCSAus	6/10	115/60	2" (3" Flanged Discharge Included)	2"	10.3	155	127	98	70	29	28	12.1	10	63	14.8	12.25	10.8
ES60W1-20	511543	cCSAus	6/10	115/60	2" (3" Flanged Discharge Included)	2"	10.3	155	127	98	70	29	28	12.1	20	66	14.8	12.25	10.8
ES60W2-20	511583	cCSAus	6/10	230/60	2" (3" Flanged Discharge Included)	2"	5.2	155	127	98	70	29	28	12.1	20	66	14.8	12.25	10.8
ES60D1-10	511562	cCSAus	6/10	115/60	2" (3" Flanged Discharge Included)	2"	10.3	155	127	98	70	29	28	12.1	10	63	14.8	12.25	10.8
ES60D1-20	511563	cCSAus	6/10	115/60	2" (3" Flanged Discharge Included)	2"	10.3	155	127	98	70	29	28	12.1	20	66	14.8	12.25	10.8
ES60D2-20	511584	cCSAus	6/10	230/60	2" (3" Flanged Discharge Included)	2"	5.2	155	127	98	70	29	28	12.1	20	66	14.8	12.25	10.8



## Construction

Motor Housing	Epoxy coated cast iron
Impeller Material	Epoxy coated cast iron
Impeller Type	Two-vane, non-clog
Volute	Epoxy coated cast iron
Power Cord	16/3 SJTW-A
Mechanical Shaft Seal	Nitrile with carbon and ceramic faces
Fasteners	Stainless steel
Shaft	Cold rolled steel
Bearings	Upper and lower ball bearings