



WALL MOSAIC























2 x 5 PICKET MOSAIC 12 x 11 SHEET







AT21 Nordic Sand



AT22 Ideal Gray



AT23 Classic Blue



AT24 Deep Blue



AT25 Metallic Vibe

2 x 4 HERRINGBONE MOSAIC 14 x 12 SHEET



AT20 Elegant White



AT21 Nordic Sand



AT22 Ideal Gray



AT23 Classic Blue



AT24 Deep Blue




AT25 Metallic Vibe

2 x 4 BRICK-JOINT MOSAIC 12 x 12 SHEET



AT20 Elegant White




AT21 Nordic Sand



AT22 Ideal Gray



AT23 Classic Blue



AT24 Deep Blue



AT25 Metallic Vibe

1-1/2 x 1-1/2 HEXAGON MOSAIC 12 x 10 SHEET




AT20 Elegant White



AT21 Nordic Sand



AT22 Ideal Gray



AT23 Classic Blue



AT24 Deep Blue



AT25 Metallic Vibe

































MOSAIC

SIZES

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
2 x 5 Picket Mosaic*	12-1/4" x 11-1/8" Sheet (31.12 cm x 27.94 cm Sheet)	1/4"	8.76	12
2 x 4 Herringbone Mosaic*	14" x 12" Sheet (35.56 cm x 30.48 cm Sheet)	1/4"	8.04	12
2 x 4 Brick-Joint Mosaic*	12" x 12" Sheet (30.48 cm x 30.48 cm Sheet)	1/4"	9.96	12
1-1/2 x 1-1/2 Hexagon Mosaic *	11-3/8" x 10-1/4" Sheet (28.89 cm x 26.04 cm Sheet)	1/4"	9.72	12

^{*} Dot-mounted

TRIM

Description	Number	Size	Shape
Jolly	S1/212J	1/2 x 12	

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	
Wet & Level - Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	
Countertops	N/A	
Pool Linings	N/A	*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit marazzitile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior wall applications in non-freezing climates only, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation		
1/8"	Medium Variation (AT20, AT21, AT22, AT23, AT24)		
1/0	High Variation (AT25)		

PERFORMANCE CHARACTERISTICS

	ASTM#	Jolly Result	Mosaic Result
Water Absorption	C373	< 20.0%	< 3.0%
Breaking Strength	C648	120 - 230 lbs	250 lbs
Scratch Hardness	MOHS	4.0 - 6.0	4.0 - 6.0
Chemical Resistance	C650	Resistant	Resistant

For additional information on test results, visit us at: marazzitile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: marazzitile.com/Factors.

FEATURES



POST-CONSUMER RECYCLED MATERIALS

REVEAL IMAGING®



PRE-CONSUMER RECYCLED MATERIALS





All or select items within this series meet the requirements for these qualifications. For more information visit marazzitile.com.

^{*} Mosaic tile only