


## Lighting Your Life Since 1970

Product Specifications - 12402UDBK		
Job Name:	Job Type:	
Quantity:	Comments	



12402UDBK **Norwood 1-Light Pendant** 



**Finish** Black

Lampin

C	las	·c/	Сh	2	d	è
G	as	3/1	JII.	a	u	5

**Product Category** Single Pendant

N/A

Lamping		Measurements	
Number of Bulbs	1	Width	13.50"
Light Type	Fluorescent	Height	16.00"
Bulb Type	GU24	Length	13.50"
Max Bulb Wattage	18	Extension	N/A
Max Fixture Wattage	18	Back Plate Width	N/A
Rated Life		Back Plate Height	N/A
Rated Lumens	±1,164	НСО	N/A
Color Temp		Min Overall Height	0.00"
Bulb(s)	Included	Max Overall Height	136.00"
Light Up/Down	N/A	Hanging Weight	1.54 lbs
Beam Spread	N/A	Height Adjustable	N/A
CRI	N/A	Slope	120°
Photo Cell Included	N/A	Chain Length	N/A
Ballast/Driver/Transformer	No	Wire Length	N/A
Dimmable	N/A	Canopy Width	N/A
		Canopy Height	N/A

Shipping	
Carton Weight	4.31 lbs
Carton Width	15"
Carton Height	17"
Carton Length	15"
Carton Cubic Feet	2.03
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification		Other		Equivalents
Safety Rating	Dry	UPC Code	783209117136	Incandescen
Energy Star	No	Shades Included	N/A	Fluorescent \
CA Title 24	Yes	Crystals Included	N/A	
CA Title 20	No	Diffuser Included	N/A	
ADA	No	Conversion Kit	N/A	
Dark Sky	N/A	Material	N/A	

**Canopy Length** 

=40.0000	
Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2015 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.