

Lighting Your Life Since 1970

Product Specifications - 214510FGS			
Job Name: Job Type:			
Quantity:	Comments		
1			



214510FGS

Diamond 1-Light Flush Mount

FinishGolden Silver

Lamping

Number of Bulbs	1
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	100
Max Fixture Wattage	100
Rated Life	±2,500 Hours
Rated Lumens	±1,150
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

las			

Measurements	
Width	12.50"
Height	9.50"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	7.70 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A

Product Category

Flush Mount

	Shipping	
"	Carton Weight	7.70 lbs
"	Carton Width	16"
4	Carton Height	12"
4	Carton Length	16"
4	Carton Cubic Feet	1.78
4	Master Pack	1
4	Master Pack Weight	N/A
4	Master Pack Width	N/A
4	Master Pack Height	N/A
s	Master Pack Length	N/A
4	Master Cubic Feet	N/A
4	UPS Shippable	Yes
4	-	

Certification	Other		Equival
Safety Rating	Dry LIPC Code	783209087477	Incande

Canopy Length

Safety Rating	Dry	UPC Code	783209087477
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Metal

⊨a	uı	val	en	ts

N/A

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2014 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.