

## Lighting Your Life Since 1970

Product Specifications - 85120ICSN		
Job Name:	Job Type:	
Quantity:	Comments	



## 85120ICSN **Basix EE 2-Light Semi-Flush Mount**



**Product Category Finish** Glass/Shade Semi-Flush Mount Satin Nickel

Lamping
Number of Bulbs
Light Type

Number of Bulbs	2
Light Type	Fluorescent
Bulb Type	GU24
Max Bulb Wattage	13
Max Fixture Wattage	26
Rated Life	±10,000 Hours
Rated Lumens	±1,800
Color Temp	±2,700 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	81-82
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	No

Measurements	
Width	14.00"
Height	10.00"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	4.41 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shipping	
Carton Weight	4.41 lbs
Carton Width	15"
Carton Height	11"
Carton Length	15"
Carton Cubic Feet	1.41
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Safaty Bating	Dry IIPC Code	792200059592 Incondescen
Certification	Other	Equivalents

Safety Rating	Dry	UPC Code	783209058583	Ir
Energy Star	Yes	Shades Included	N/A	F
CA Title 24	Yes	Crystals Included	N/A	
CA Title 20	No	Diffuser Included	N/A	
ADA	No	Conversion Kit	N/A	
Dark Sky	N/A	Material	Iron	

Incandescent Watts	164
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2014 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.