

Lighting Your Life Since 1970

Product Specifications - 93000CLPC		
Job Name:	Job Type:	
Quantity:	Comments	



93000CLPC

Flask 1-Light LED Mini Pendant

Finish Polished Chrome

Lamping Number of Bulbs

Number of Buids	Į.
Light Type	LED
Bulb Type	LED
Max Bulb Wattage	2.8
Max Fixture Wattage	2.8
Rated Life	±40,000 Hours
Rated Lumens	±196
Color Temp	±3,000 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	Yes
Dimmable	Standard/Lutron® or Leviton® CL

(GI	a	s	S	S	h	a	d	е

Clear

	 ~			nts
IVI	SII	rer	ne	nts

modean emente	
Width	4.50"
Height	7.00"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	51.00"
Hanging Weight	4.61 lbs
Height Adjustable	Yes
Slope	120°
Chain Length	N/A
Wire Length	180"
Canopy Width	N/A
Canopy Height	N/A

Product Category Mini Pendant

Shinning

Snipping	
Carton Weight	4.61 lbs
Carton Width	7'
Carton Height	7'
Carton Length	11'
Carton Cubic Feet	0.30
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Safety Rating	Dry
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No
Dark Sky	N/A

Canopy Length

Other	
UPC Code	783209105065
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Metal

Equivalents

N/A

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2014 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.