


Lighting Your Life Since 1970

Product Specifications - 39104BCTXBPN Job Name: Job Type: Quantity: Comments



39104BCTXBPN Equinox LED Pendant



Finish
Textured Black / Polished Nickel

Glass/Shade Beveled Crystal *max overall height **Product Category**Single Pendant

La	ing	

Lamping	
Number of Bulbs	15
Light Type	LED
Bulb Type	G9
Max Bulb Wattage	2.3
Max Fixture Wattage	34.5
Rated Life	
Rated Lumens	±2,850
Color Temp	3500K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	90+
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Yes

Measurements Width

Width	25.00"
Height	29.75"
Length	25.00"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	31.50"
Max Overall Height	110.25"
Hanging Weight	22.00 lbs
Height Adjustable	Yes
Slope	N/A
Chain Length	36"
Wire Length	120"
Canopy Width	5.75"
Canopy Height	1.40"
Canopy Length	5.75"

Shinnina

Shipping	
Carton Weight	27.70 lbs
Carton Width	26'
Carton Height	32'
Carton Length	29'
Carton Cubic Feet	13.87
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Oversize

Certification

Safety Rating	Dry	UPC Code	783209127197
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Steel+Crystal

Other

Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2016 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.