

# COUNTERMAX MX-L-24-SS | 24V SLIM STICK

89800 | 89801 | 89802 | 89803 | 89804

- Aluminum finish with Black accessories
- Even distribution of LED diffused through opal white lens
- 24V system must be paired with driver accessories
- Adjustable mounting clips allow for angled installation
- Dimmable with LED dimmers and Touch dimmer Energy Star Certified
- Title 24 JA8 listed=
- 3000K Color Temperature
- CRI 90+

Job Name : \_\_\_\_\_  
 Job Type : \_\_\_\_\_  
 Quantity : \_\_\_\_\_  
 Comments : \_\_\_\_\_




• Includes adjustable mounting clips




## PRODUCT DESCRIPTION

Narrow Aluminum channels of LED are easily concealed in an economical way to tackle your task lighting. Installation is simple with an adjustable bracket that allows you to direct the light to where you need it, and a simple plug-in or hard wire power supply. Available in lengths from 6" to 48" and varies accessories, Slim Stick is the easy solution for your task lighting installation.

### LED PROFILE



### IN-LINE DIMMER



## MEASUREMENTS

MODEL	DIMENSION	BULB TYPE	COLOR TEMP	CRI	LUMENS		DIMMABLE	V INPUT
					RATED	DELIVERED		
89800	0.75"W x 0.5"H x 6"L	3W Integrated LED	3000K	90+	350	195	LED	24V
89801	0.75"W x 0.5"H x 12"L	5W Integrated LED	3000K	90+	700	395	LED	24V
89802	0.75"W x 0.5"H x 24"L	10W Integrated LED	3000K	90+	1050	780	LED	24V
89803	0.75"W x 0.5"H x 36"L	15W Integrated LED	3000K	90+	1400	1170	LED	24V
89804	0.75"W x 0.5"H x 48"L	20W Integrated LED	3000K	90+	1750	1560	LED	24V

## LAMPING

(SEE COMPATIBLE DRIVERS AND ACCESSORIES ON NEXT PAGE FOR DIMMING INFORMATION)

## FINISHES:

**ALUMINUM (AL)**

## MATERIAL

Aluminum

## RATINGS

cETLus  
 Dry Location  
 Energy Star  
 JA8 Listed



## ADDITIONAL

OPERATING TEMPERATURE: -20°  
 C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



**WESTERN DISTRIBUTION CENTER (HEADQUARTER)**  
 253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746  
**EASTERN DISTRIBUTION CENTER**  
 101 GARDNER PARK | PEACHTREE CITY, GA 30269  
 P. 626.956.4200 | F. 626.956.4225 | maximlighting.com

## 24V CONSTANT VOLTAGE LED DRIVERS


### Hard Wired Power Supplies



Hard Wired Driver

**DHW898-2496BK**  
W8.5" H3.25"

100-295V input  
96W MAX  
Includes Plug in Connector  
Compatible with Triac or ELV



Dimmable Driver Switch

**SWT898-2460WT**  
60W MAX  
**SWT898-2475WT**  
75W MAX  
2"W x 2.25"L x 4.25"H

### Plug-in Power Supplies

\*can be used with in-line dimmer switch



**89811BK**  
24W Plug-In Driver Non-dimming



**DRV898-2460BK (89812BK)**  
60W Plug-In Driver Non-Dimming



**89814BK**  
96W Plug-In Driver Non Dimming



**89835AL**  
In-Line Dimmer Switch  
On/Off and Brightness Control

## CONNECTING CORDS



**89820BK**  
2"



**89822BK 12"**  
\*includes  
ON/OFF switch



**CRD898-18BK**  
18"



**CRD898-36BK**  
36"



**CRD898-60BK**  
60"



**89833BK**  
LOW VOLTAGE SPLICE BOX  
L 1.75" x W 2.25" x H 0.5"



90° CONNECTOR  
**89830BK**  
L



**89831BK**  
R

Always consult a qualified electrician before installing any lighting product.