

Lighting Your Life Since 1970

Product Specifications - 1066BK			
Job Name:	Job Type:		
Quantity:	Comments		



Senator 1-Light Outdoor Wall Lantern

N/A

N/A

N/A

N/A

Finish Glass/Shade **Product Category** Outdoor Wall Mount Black Seedy

Measurements

Wire Length

Canopy Width

Canopy Height

Canopy Length

L	am	р	ing	7
Ν	um	ıb	er	(
			_	

=amping	
Number of Bulbs	1
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	100
Max Fixture Wattage	100
Rated Life	±2,500 Hours
Rated Lumens	±1,150
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

Width	7.0"
Height	15.0"
Length	N/A
Extension	8"
Back Plate Width	4.3"
Back Plate Height	6.3"
HCO	2.5"
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	3.1 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
mani Lengui	IN/A

Shipping	
Carton Weight	3.1 lbs
Carton Width	8'
Carton Height	17'
Carton Length	9'
Carton Cubic Feet	0.75
Master Pack	6
Master Pack Weight	20.9 lbs
Master Pack Width	19.7
Master Pack Height	17.5
Master Pack Length	25.8
Master Cubic Feet	5.15
UPS Shippable	Yes

Certification		Other		Equivalents	
Safety Rating	Wet	UPC Code	783209106611	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	Die Cast Aluminum		

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.