

Lighting Your Life Since 1970

Product Specifications - 13583CFAF			
Job Name: Job Type:			
Quantity:	Comments		



13583CFAF

Augusta 3-Light Invert Bowl Pendant

Finish	Glass/Shade	Product Category
Auburn Florentine	Cafe	Invert Bowl Pendant

Number of Bulbs	3
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	100
Max Fixture Wattage	300
Rated Life	±2,500 Hours
Rated Lumens	±3,450
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

Measurements	
Width	31.0"
Height	37.0"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
НСО	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	29.0 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	36"
Wire Length	180"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shinning

Shipping	
Carton Weight	29.0 lbs
Carton Width	30"
Carton Height	17"
Carton Length	33"
Carton Cubic Feet	9.65
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification Other **Equivalents**

Oct uncution		Othici		Equivalento	
Safety Rating	Dry	UPC Code	783209058743	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	Optional		
CA Title 20	No	Diffuser Included	Yes		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	Steel		

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.