

Lighting Your Life Since 1970

Product Specifications - 12029AD			
Job Name:	Job Type:		
Quantity:	Comments		



12029AD

Hampton 6-Light Entry Foyer Pendant

Finish Auburn Dusk

Lamping

G	па	SS	5/S	sn	a	α	Е

Product Category

Entry Foyer Pendant

Lamping	
Number of Bulbs	6
Light Type	Incandescent
Bulb Type	CA
Max Bulb Wattage	60
Max Fixture Wattage	360
Rated Life	±1,500 Hours
Rated Lumens	±4,032
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard Dimmer

Measurements	
Width	26.00"
Height	33.00"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
НСО	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	13.67 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	36"
Wire Length	180"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

	Shipping	
"	Carton Weight	13.67 lbs
"	Carton Width	29"
١	Carton Height	10"
١	Carton Length	33"
١	Carton Cubic Feet	5.44
١	Master Pack	1
١	Master Pack Weight	N/A
١	Master Pack Width	N/A
١	Master Pack Height	N/A
3	Master Pack Length	N/A
١	Master Cubic Feet	N/A
١	UPS Shippable	Yes

CE	rtifi	Lau	UII

Certification Other	
Safety Rating Dry UPC Code 7832090646	76
Energy Star No Shades Included N	1/A
CA Title 24 No Crystals Included Y	'es
CA Title 20 No Diffuser Included N	1/A
ADA No Conversion Kit N	I/A
Dark Sky N/A Material Ste	eel

Εq	Jui	val	len	ts

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2014 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.