

## PFD 104 SCVi XXL

Fully integrated Full-sizedishwasher with 3D MultiFlex cutlery tray for large loads of dishware in households, offices and utility areas.



- Wash performance: 16 place settings in just 52min.\*
- Flexible loading of wash items for the best cleaning results
- Door opens automatically after two knocks – Knock2open
- Everything completely dry – AutoOpen assisted drying
- Innovative design and maximum convenience – 3D MultiFlex Tray

EAN: 4002516366881 / material number: 11605450

<b>Model and design</b>	
Design	Fully integrated dishwasher
Line	ProfiLine
Wash system	Fresh water
Number of levels	2
Front	Without front
Side walls	Galvanised
Drying	AutoOpen assisted drying Extra drying Active condensation drying
Minimum front panel weight in lbs	12 (5)
Maximum front panel weight in lbs	27 (12)
<b>Application</b>	
Suitable for retirement and nursing homes	•
Suitable for hospitals	•
Suitable for Bed & Breakfast	•
Suitable for child care facilities	•
Suitable for universities and schools	•
Suitable for offices	•
Suitable for domestic use	•
Suitable for small businesses	•
Suitable for sports clubs	•
<b>Performance data</b>	
Tested virucidal efficacy	•
Circulation pump, Qmax in gal/min (l/min)	0.0 (75)
Shortest program duration in min.	52
Maximum final rinse temperature in °F (°C)	180 (82)
Cleaning performance, place settings/cycle	16
Service life in wash cycles	12,500
<b>Controls</b>	
Control system	Electronic controls
Program selection	Program Selector Buttons
Max. delay start in h	24
Countdown indicator	•
Program sequence indicator	•
Check filter indicator	•
Choice of display language	•
<b>Standard electrical connection</b>	
Electrical connection	AC 120V 60HZ
Heater rating in kW	1.30
Total connected load in kW	1.40
Fuse rating in A	15
Length of power cord in ft (m)	5 (1.70)
<b>Possible voltage variant 1</b>	
Electrical connection	2N AC 120/208-240V, 60HZ
Heater rating in kW	3,5-3,8
Total connected load in kW	3,70-4,00
Fuse rating in A	30

## PFD 104 SCVi XXL

Fully integrated Full-sizedishwasher with 3D MultiFlex cutlery tray for large loads of dishware in households, offices and utility areas.



<b>Water connection/drainage</b>	
Cold or hot water [number]	1
Required flow pressure in bar	0,30-10,00
Drain hose [DN]	22
Maximum delivery head for drain pump in inches (cm)	39 3/8 (100)
Integrated water softener	•
Maximum water hardness in gpg (mmol/l)	0.000 (6.50)
Water protection system	Waterproof system
Length of water inlet hose in inches	59 1/8 (150)
Length of water drain hose in inches	59 1/8 (150)
<b>Dimensions and weight</b>	
External dimensions, net height in inches	33 3/8 (845)
External dimensions, net width in inches	23 5/8 (598)
External dimensions, net depth in inches	22 1/2 (570)
External dimensions, gross height in inches	37 7/8 (960)
External dimensions, gross width in inches	26 1/2 (670)
External dimensions, gross depth in inches	27 5/8 (700)
Usable space in wash cabinet, height in inches (mm)	22 7/8 (580)
Usable space in wash cabinet, width in inches (mm)	20 1/8 (510)
Usable space in wash cabinet, depth of upper basket in inches (mm)	17 3/4 (450)
Usable space in wash cabinet, depth of lower basket in inches (mm)	17 3/4 (450)
In-feed height above floor in inches (mm)	8 3/8 (210)
Net weight in lbs.	113 (51)
Gross weight in lbs.	128 (58)
Maximum floor loading in p/force	1,000
<b>Emission levels</b>	
Sound power (LwA) in dB(A) re 1 pW	45.0
<b>Programs</b>	
Universal	•
Short/QuickIntenseWash	•
SaniWash	•
Cold/pre-rinse/Rinse&Hold	•
Glasses	•
Plastic	•
EnergySave/Economy	•
Intensive	•
<b>Basket design</b>	
MaxiComfort baskets	•
Flexible FlexLine Baskets	•
FlexCare glass holder [quantity]	4
FlexCare cup rack [quantity]	2
Height-adjustable upper basket	•
Patented 3D MultiFlex Tray	•

## PFD 104 SCVi XXL

Fully integrated Full-sizedishwasher with 3D MultiFlex cutlery tray for large loads of dishware in households, offices and utility areas.



<b>Features</b>	
Commercial-grade electrical connection	•
1 Combi dispenser/door for powder and liquid media	•
Wash cabinet made from high-quality stainless steel.	•
LED Lighting	•
Knock2open	•
AutoOpen assisted drying	•
AutoClose	•
EcoFeedback	•
Perfect GlassCare	•
Adjustable final rinse temperature	•
Optical interface	•
SmartStart	•
FlexiTimer with EcoStart	•
<b>Connection options</b>	
External dispensing module for liquid cleaning agent	•
<b>Test certificates and symbols</b>	
CE	•
Complies with Machinery Directive 2006/4 2/EC	•
VDE	•
EMC radio suppressed	•
EN 1717	•
UL	•