

KMR 1135-3 G GR EDST/CLST RangeTop



- Professional design – 36 (914) in (mm) wide in stainless steel with Clean Touch Steel™ finishing
- Direct control – metal knobs with light ring
- Easy cleaning – ComfortClean dishwasher-safe grates
- Broad performance spectrum – burner w. up to 19,500 BTU (5.7 kW)
- Convenient and safe – automatic re-ignition for all burners

EAN: 4002516495383 / Material number: 11852380 / Old Material Number: 26113570USA

Heating type	
Fuel type	Gas
Construction type	
Rangetop	•
Design	
Casing	Stainless steel
Front panel	CleanSteel
Genuine metal knobs	•
Cast iron pot rest (matte black enameled)	•
Ring features	
Number of gas burners	4
Number of grill surfaces	1
1st cooking zone/cooking area	
Position	front left
Type	Ultra high-speed burner
Minimum power output in BTU/hr	1700
Maximum power output in BTU/hr	19500
Max. rating in W	5700
2nd cooking zone/cooking area	
Position	rear left
Type	High-speed burner
Minimum power output in BTU/hr	1200
Maximum power output in BTU/hr	12500
Max. rating in W	2300
3rd cooking zone/cooking area	
Position	Centered
Type	Grill surface
Minimum power output in BTU/hr	13000
Maximum power output in BTU/hr	19000
Max. rating in W	5600
4th cooking zone/cooking area	
Position	rear right
Type	High-speed burner
Minimum power output in BTU/hr	1700
Maximum power output in BTU/hr	13600
Max. rating in W	2600
5th cooking zone/cooking area	
Position	front right
Type	Ultra high-speed burner
Minimum power output in BTU/hr	1700
Maximum power output in BTU/hr	19500
Max. rating in W	5700
8th cooking zone/cooking area	
True Simmer function	•
Width of broil surface in in.(mm)	11 1/4 (284)
Depth of broil surface in in.(mm)	22 1/8 (560)
Control panel	
Operation via genuine metal knobs with backlit	•
Cleaning convenience	
Dishwasher-safe trivets	•

KMR 1135-3 G GR EDST/CLST RangeTop



EAN: 4002516495383 / Material number: 11852380 / Old Material Number: 26113570USA

Single-piece cooktop surround

•

Safety


Automatic re-ignition

•

Technical data

Dimensions (width) in in. (mm)	36 (914)
Height in in. (mm)	7 5/8 (191)
Dimensions (depth) in in. (mm) with bullnose	27 1/4 (692)
Dimensions (depth) in in. (mm) without bullnose	25 5/8 (650)
Weight in lbs. (kg)	132 (60)
Total output in BTU/hr	84100
Total connected load in kW	0.00
Voltage in V	120
Fuse rating in A	10
Number of phases	1
Power cord length in in. (m)	3 (1.2)

KMR 1135-3 G GR EDST/CLST RangeTop



KMR1134, KMR1135, KMR1136, KMR1134-3, KMR1135-3, KMR1136-3 (Installation drawing)

1) Side view, 2) Front view, 3) Rear view, 4) Gas Connection, 5) Electrical connection