

DA 1280 30-inch built-under ventilation hood with energy-efficient LED lighting and sliding switch for simple operation.




- Puristic design space-saving solution 30 (760) in (mm) wide
- Powerful ?? in Booster level
- Efficient filtration- 10-ply stainless steel grease filters
- Safe and easy to clean Miele CleanCover
- Suitable for every home vented or recirculating

EAN: 4002515774403 / Material number: 10451490 / Old Material Number: 28128055USA

Built-under ventilation hood Operating modes Recirculated mode OdorFree charcoal filter (order separately) DKF 18-900 Design Color Stainless ste Customization possible on request User convenience Recessed knob controls Power levels (number excl. Intensive) 3 Slide switch CleanCover Filter system Number of dishwasher-safe stainless-steel grease filters Lighting LED Number x W Light intensity in Lx Color temperature in K Blower Single-action blower AC motor Exhaust air Air throughput Canopy width in in.(mm) Canopy width in in.(mm) S1 (760) Canopy depth in in.(mm) S1 (300) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Fuse cating in A Number of phases Frequency in Hz Installation note Vent connection at top	
Recirculated mode OdorFree charcoal filter (order separately) DKF 18-900 Design Color Stainless ste Customization possible on request User convenience Recessed knob controls Power levels (number excl. Intensive) Slide switch CleanCover Filter system Number of dishwasher-safe stainless-steel grease filters Lighting LED Number x W Light intensity in Lx Color temperature in K Blower Single-action blower AC motor Exhaust air Air throughput Technical data Canopy width in in.(mm) Canopy height in in.(mm) S1 (125) Canopy depth in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Fuse rating in A Number of phases Frequency in Hz Installation note	
Recirculated mode OdorFree charcoal filter (order separately) DKF 18-900 Design Color Stainless ste Customization possible on request User convenience Recessed knob controls Power levels (number excl. Intensive) Slide switch CleanCover Filter system Number of dishwasher-safe stainless-steel grease filters Lighting LED Number x W Light intensity in Lx Color temperature in K Blower Single-action blower AC motor Exhaust air Air throughput Technical data Canopy width in in.(mm) Canopy height in in.(mm) Sq. (760) Canopy depth in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Fuse rating in A Number of phases Frequency in Hz Installation note	
Design Color Stainless stee Customization possible on request User convenience Recessed knob controls Power levels (number excl. Intensive) Slide switch CleanCover Filter system Number of dishwasher-safe stainless-steel grease filters Lighting LED Variable Single-action blower AC motor Exhaust air Canopy width in in.(mm) Canopy height in in.(mm) Pay 3/4 (500) Ret weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Frequency in Hz Installation note	itted
Design Color Stainless stee Customization possible on request User convenience Recessed knob controls Power levels (number excl. Intensive) Slide switch CleanCover Filter system Number of dishwasher-safe stainless-steel grease filters Lighting LED Variable Single-action blower AC motor Exhaust air Canopy width in in.(mm) Canopy height in in.(mm) Pay 3/4 (500) Ret weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Frequency in Hz Installation note	
Color Stainless ste Customization possible on request User convenience Recessed knob controls Power levels (number excl. Intensive) Slide switch CleanCover Filter system Number of dishwasher-safe stainless-steel grease filters Lighting LED Number x W Light intensity in Lx Color temperature in K Blower Single-action blower AC motor Exhaust air Air throughput Technical data Canopy width in in.(mm) Canopy height in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Frequency in Hz Installation note	
Customization possible on request User convenience Recessed knob controls Power levels (number excl. Intensive) 3 Slide switch CleanCover Filter system Number of dishwasher-safe stainless-steel grease filters Lighting LED Number x W 2 x 3 W Light intensity in Lx Color temperature in K 3000 Kelvin Blower Single-action blower AC motor Exhaust air Air throughput Values upon Technical data Canopy width in in.(mm) Canopy height in in.(mm) Solution Standard plug fitted Total connected load in kW Voltage in V Frequency in Hz Installation note	el
User convenience Recessed knob controls • Power levels (number excl. Intensive) 3 Slide switch • CleanCover • Filter system *** Number of dishwasher-safe stainless-steel grease filters 3 Lighting *** Light intensity in Lx 2 x 3 W Light intensity in Lx 275 lx Color temperature in K 3000 Kelvin Blower *** Single-action blower • AC motor • Exhaust air Values upon Air throughput Values upon Technical data *** Canopy width in in.(mm) 30 (760) Canopy height in in.(mm) 5 (125) Canopy depth in ins.(kg) 29 (12.9) Length of electrical wire in ft (m) 4 (1.5) Standard plug fitted • Total connected load in kW 0.28 Voltage in V 120 Fuse rating in A 15 Number of phases 1 Frequency in Hz 60 Installation note 60	
Recessed knob controls	
Power levels (number excl. Intensive) Slide switch CleanCover Filter system Number of dishwasher-safe stainless-steel grease filters Lighting LED Number x W Light intensity in Lx Color temperature in K Blower Single-action blower AC motor Exhaust air Air throughput Values upon Technical data Canopy width in in.(mm) Canopy height in in.(mm) Canopy depth in in.(mm) Standard plug fitted Total connected load in kW Voltage in V Fuse rating in A Number of phases Frequency in Hz Installation note	
Slide switch CleanCover Filter system Number of dishwasher-safe stainless-steel grease filters Lighting LED Number x W Light intensity in Lx Color temperature in K Blower Single-action blower AC motor Exhaust air Air throughput Values upon Technical data Canopy width in in.(mm) Canopy height in in.(mm) Sight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Frequency in Hz Installation note	
CleanCover Filter system Number of dishwasher-safe stainless-steel grease filters Lighting LED Number x W Light intensity in Lx Color temperature in K Blower Single-action blower AC motor Exhaust air Air throughput Values upon Technical data Canopy width in in.(mm) Canopy height in in.(mm) Canopy depth in in.(mm) Sitandard plug fitted Total connected load in kW Voltage in V Fuse rating in A Number of phases I Frequency in Hz Installation note	
Filter system Number of dishwasher-safe stainless-steel grease filters Lighting LED Number x W Light intensity in Lx Color temperature in K Blower Single-action blower AC motor Exhaust air Air throughput Technical data Canopy width in in.(mm) Canopy height in in.(mm) Canopy depth in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Frequency in Hz Installation note	
Number of dishwasher-safe stainless-steel grease filters Lighting LED Number x W Light intensity in Lx Color temperature in K Blower Single-action blower AC motor Exhaust air Air throughput Technical data Canopy width in in.(mm) Canopy height in in.(mm) Canopy depth in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Frequency in Hz Installation note	
LED LED Number x W Light intensity in Lx Color temperature in K Blower Single-action blower AC motor Exhaust air Air throughput Technical data Canopy width in in.(mm) Canopy height in in.(mm) Canopy depth in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Values upon 9 (12.9) 4 (1.5) Standard plug fitted Total connected load in kW Voltage in V Fuse rating in A Number of phases 1 Frequency in Hz Installation note	
LED • Number x W 2 x 3 W Light intensity in Lx 275 lx Color temperature in K 3000 Kelvin Blower • Single-action blower • AC motor • Exhaust air Values upon Air throughput Values upon Technical data * Canopy width in in.(mm) 30 (760) Canopy height in in.(mm) 5 (125) Canopy depth in in.(mm) 19 3/4 (500) Net weight in lbs. (kg) 29 (12.9) Length of electrical wire in ft (m) 4 (1.5) Standard plug fitted • Total connected load in kW 0.28 Voltage in V 120 Fuse rating in A 15 Number of phases 1 Frequency in Hz 60 Installation note •	
Number x W 2 x 3 W Light intensity in Lx 275 lx Color temperature in K 3000 Kelvin Blower • Single-action blower • AC motor • Exhaust air Values upon Air throughput Values upon Technical data Canopy width in in.(mm) 30 (760) Canopy height in in.(mm) 5 (125) Canopy depth in in.(mm) 19 3/4 (500) Net weight in lbs. (kg) 29 (12.9) Length of electrical wire in ft (m) 4 (1.5) Standard plug fitted • Total connected load in kW 0.28 Voltage in V 120 Fuse rating in A 15 Number of phases 1 Frequency in Hz 60 Installation note 60	
Light intensity in Lx 275 lx Color temperature in K 3000 Kelvin Blower • Single-action blower • AC motor • Exhaust air Values upon Air throughput Values upon Technical data 20 (760) Canopy width in in.(mm) 5 (125) Canopy height in in.(mm) 19 3/4 (500) Net weight in lbs. (kg) 29 (12.9) Length of electrical wire in ft (m) 4 (1.5) Standard plug fitted • Total connected load in kW 0.28 Voltage in V 120 Fuse rating in A 15 Number of phases 1 Frequency in Hz 60 Installation note 60	
Color temperature in K 3000 Kelvin Blower • Single-action blower • AC motor • Exhaust air Values upon Air throughput Values upon Technical data 20 (760) Canopy width in in.(mm) 5 (125) Canopy height in in.(mm) 19 3/4 (500) Net weight in lbs. (kg) 29 (12.9) Length of electrical wire in ft (m) 4 (1.5) Standard plug fitted • Total connected load in kW 0.28 Voltage in V 120 Fuse rating in A 15 Number of phases 1 Frequency in Hz 60 Installation note 60	
Blower • Single-action blower • AC motor • Exhaust air Values upon Air throughput Values upon Technical data 30 (760) Canopy width in in.(mm) 5 (125) Canopy height in in.(mm) 19 3/4 (500) Net weight in lbs. (kg) 29 (12.9) Length of electrical wire in ft (m) 4 (1.5) Standard plug fitted • Total connected load in kW 0.28 Voltage in V 120 Fuse rating in A 15 Number of phases 1 Frequency in Hz 60 Installation note •	
Single-action blower ● AC motor ● Exhaust air Values upon Technical data Values upon Canopy width in in.(mm) 30 (760) Canopy height in in.(mm) 5 (125) Canopy depth in in.(mm) 19 3/4 (500) Net weight in lbs. (kg) 29 (12.9) Length of electrical wire in ft (m) 4 (1.5) Standard plug fitted • Total connected load in kW 0.28 Voltage in V 120 Fuse rating in A 15 Number of phases 1 Frequency in Hz 60 Installation note •	
AC motor Exhaust air Air throughput Values upon Technical data Canopy width in in.(mm) Canopy height in in.(mm) Canopy depth in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Total connected load in kW Voltage in V Fuse rating in A Number of phases Installation note Values upon 30 (760) 5 (125) 29 (12.5) 4 (1.5) 5 (125) 29 (12.9) 4 (1.5) 5 (125) 29 (12.9) 4 (1.5) 5 (125) 29 (12.9) 4 (1.5) 5 (125) 29 (12.9) 4 (1.5) 5 (125) 29 (12.9) 4 (1.5) 5 (1.5) 6 (
Exhaust air Values upon Technical data 30 (760) Canopy width in in.(mm) 5 (125) Canopy depth in in.(mm) 19 3/4 (500) Net weight in lbs. (kg) 29 (12.9) Length of electrical wire in ft (m) 4 (1.5) Standard plug fitted • Total connected load in kW 0.28 Voltage in V 120 Fuse rating in A 15 Number of phases 1 Frequency in Hz 60 Installation note 60	
Air throughput Values upon Technical data 30 (760) Canopy width in in.(mm) 5 (125) Canopy depth in in.(mm) 19 3/4 (500) Net weight in lbs. (kg) 29 (12.9) Length of electrical wire in ft (m) 4 (1.5) Standard plug fitted • Total connected load in kW 0.28 Voltage in V 120 Fuse rating in A 15 Number of phases 1 Frequency in Hz 60 Installation note Installation note	
Technical data 30 (760) Canopy width in in.(mm) 5 (125) Canopy depth in in.(mm) 19 3/4 (500) Net weight in lbs. (kg) 29 (12.9) Length of electrical wire in ft (m) 4 (1.5) Standard plug fitted ● Total connected load in kW 0.28 Voltage in V 120 Fuse rating in A 15 Number of phases 1 Frequency in Hz 60 Installation note 60	request
Canopy width in in.(mm) 30 (760) Canopy height in in.(mm) 5 (125) Canopy depth in in.(mm) 19 3/4 (500) Net weight in lbs. (kg) 29 (12.9) Length of electrical wire in ft (m) 4 (1.5) Standard plug fitted ● Total connected load in kW 0.28 Voltage in V 120 Fuse rating in A 15 Number of phases 1 Frequency in Hz 60 Installation note ■	. oquoot
Canopy height in in.(mm) 5 (125) Canopy depth in in.(mm) 19 3/4 (500) Net weight in lbs. (kg) 29 (12.9) Length of electrical wire in ft (m) 4 (1.5) Standard plug fitted • Total connected load in kW 0.28 Voltage in V 120 Fuse rating in A 15 Number of phases 1 Frequency in Hz 60 Installation note •	
Canopy depth in in.(mm) 19 3/4 (500) Net weight in lbs. (kg) 29 (12.9) Length of electrical wire in ft (m) 4 (1.5) Standard plug fitted • Total connected load in kW 0.28 Voltage in V 120 Fuse rating in A 15 Number of phases 1 Frequency in Hz 60 Installation note ■	
Net weight in lbs. (kg) 29 (12.9) Length of electrical wire in ft (m) 4 (1.5) Standard plug fitted ● Total connected load in kW 0.28 Voltage in V 120 Fuse rating in A 15 Number of phases 1 Frequency in Hz 60 Installation note ■	
Length of electrical wire in ft (m) 4 (1.5) Standard plug fitted Total connected load in kW 0.28 Voltage in V 120 Fuse rating in A 15 Number of phases 1 Frequency in Hz 60 Installation note	
Standard plug fitted Total connected load in kW Voltage in V Fuse rating in A Number of phases 1 Frequency in Hz Installation note	
Total connected load in kW 0.28 Voltage in V 120 Fuse rating in A 15 Number of phases 1 Frequency in Hz 60 Installation note 60	
Voltage in V 120 Fuse rating in A 15 Number of phases 1 Frequency in Hz 60 Installation note 60	
Fuse rating in A 15 Number of phases 1 Frequency in Hz 60 Installation note	
Number of phases 1 Frequency in Hz 60 Installation note	
Frequency in Hz 60 Installation note	
Installation note	
veni connection at too	
Diameter of vent connection in in.(mm) 6 (150)	
Installation template •	
Standard accessories	
Recirculation deflector	
Non-return flap •	
Optional accessories	
OdorFree charcoal filter DKF 18-900	



DA 1280 30-inch built-under ventilation hood with energy-efficient LED lighting and sliding switch for simple operation.



DA 1180, Stainless steel (installation drawing)