

DA 6498 W Pure Grey
Wall ventilation hood
with energy-efficient LED lighting and touch controls for simple operation.



- Lots of headroom – 35 1/2 (899) in (mm) wide with an exclusive glass design
- Unique user convenience – Con@ctivity
- Powerful – ?? in Booster level
- Energy-efficient and quiet
- Safe and easy to clean – Miele CleanCover

EAN: 4002515961513 / Material number: 10811940 / Old Material Number: 28649860USA

Design	
Wall ventilation hood	•
Operating modes	
Recirculated mode	Can be retrofitted
OdorFree charcoal filter (order separately)	DKF 25-P
Design	
Color	Graphite grey
Edge extraction	•
User convenience	
Automatic function Con@ctivity	•
Electronic controls	•
Power levels (number excl. Intensive)	3
Touch controls	•
Programmable Intensive switch-off	•
Delayed shutdown for 5 or 15 minutes	•
Grease filter saturation indicator	•
Programmable grease filter saturation indicator	•
Programmable charcoal filter saturation indicator	•
CleanCover	•
Filter system	
Number of dishwasher-safe stainless-steel grease filters	1
Lighting	
LED	•
Number x W	2 x 3 W
Light intensity in Lx	440 lx
Color temperature in K	3500 Kelvin
Light dimmer function	•
Blower	
Dual-action blower	•
AC motor	•
Exhaust air	
Air throughput	Values upon request
Safety	
Safety shut-off	•
Single-ply safety glass (ESG)	•
Technical data	
Overall hood height for vented mode and external in inches (mm)	21 3/4 (550)
Overall hood height for recirculation and external in inches (mm)	21 3/4 (550)
Overall min. height for vented and external in in. (mm)	21 3/4 (550)
Canopy width in in.(mm)	35 1/2 (899)
Overall max. height for vented and external in in. (mm)	21 3/4 (550)
Canopy height in in.(mm)	21 3/4 (550)
Overall min. height for recirculation in in. (mm)	21 3/4 (550)
Canopy depth in in.(mm)	20 7/8 (530)
Overall max. height for recirculation in in. (mm)	21 3/4 (550)
Net weight in lbs. (kg)	56 (25.0)
Length of electrical wire in ft (m)	4 (1.5)
Standard plug fitted	•

DA 6498 W Pure Grey
 Wall ventilation hood
 with energy-efficient LED lighting and touch controls for simple operation.



EAN: 4002515961513 / Material number: 10811940 / Old Material Number: 28649860USA

Hard-wired	•
Total connected load in kW	0.35
Voltage in V	120
Fuse rating in A	15
Number of phases	1
Frequency in Hz	60
Installation note	
Vent connection at top	•
Vent connection at top and rear	•
Diameter of vent connection in in.(mm)	6 (150)
Standard accessories	
Communication module for Con@ctivity XKM 2000 DA	XKS 3000 Z
Non-return flap	•
Optional accessories	
OdorFree charcoal filter	Nein
Duct Cover	DADC 6000