

## KM 7755 FL

42-inch induction cooktop, operated with its own controls with 2 PowerFlex cooking areas for maximum performance



- Intuitive quick selection via number sequences – Smart Select
- 5 cooking zones incl. 2 high-power PowerFlex cooking areas
- With a width of 42 3/8 (1074) in (mm) for proud-mounted or flush-mounted installation
- Shortest heating-up times – TwinBooster
- Communication with the ventilation hood – automatic Con@ctivity function

EAN: 4002516611554 / Material number: 12074240 / Old Material Number: 26775570USA

<b>Heating type</b>	
Fuel type	Induction
<b>Design</b>	
Independent of oven	•
<b>Design</b>	
Elegant glass ceramic surface	•
Flush	•
Ceramic surface colour	Black
Proud installation	•
<b>Cooking zone details</b>	
No. of rings	5
Number of cooking areas	2
Maximum number of pans	5
<b>PowerFlex cooking zones</b>	
No.	4
Type	PowerFlex cooking zone
Diameter in inches	Ø 150 – 230
Power in W	2100
Booster in W	3000
TwinBooster in W	3700
<b>1st cooking zone/cooking area</b>	
Position	Left
Type	PowerFlex bridge
Size in mm	230x390
Max. Booster power rating in W	4800
Max. rating in W	3400
Max. TwinBooster power rating in W	7400
<b>2nd cooking zone/cooking area</b>	
Position	Centered
Type	Variable cooking zone
Size in mm	Ø 180-280
Max. Booster power rating in W	3000
Max. rating in W	2600
Max. TwinBooster power rating in W	3700
<b>3rd cooking zone/cooking area</b>	
Position	right
Type	PowerFlex bridge
Size in mm	230x390
Max. Booster power rating in W	4800
Max. rating in W	3400
Max. TwinBooster power rating in W	7400
<b>User convenience</b>	
Miele@home	•
Operation via sensor controls	Smart Select
Automatic function	Con@ctivity 3.0
Pan and pan size recognition	•
Display colour	Yellow
Auto heat-up	•
Stop & Go function	•
Recall function	•

## KM 7755 FL

42-inch induction cooktop, operated with its own controls  
with 2 PowerFlex cooking areas for maximum performance



EAN: 4002516611554 / Material number: 12074240 / Old Material Number: 26775570USA

Safety switch-off	•
Permanent pan recognition	•
Individual setting options (e.g. buzzers)	•
Wipe protection	•
Minute minder	•
Keep-warm function	•
<b>Cleaning convenience</b>	
Easy to clean ceramic glass	•
<b>Safety</b>	
Safety cut-out	•
Lock function	•
System lock	•
Integrated cooling blower	•
Overheating protection	•
Residual heat indicator	•
<b>Technical data</b>	
Dimensions (width) in in. (mm)	42 3/8 (1074)
Dimensions (height) in in. (mm)	3 1/8 (77)
Dimensions in mm (depth)	21 1/4 (538)
Cutout dimensions (width) in in. (mm)	40 3/4 (1035)
Cutout dimensions (depth) in in. (mm)	20 1/2 (518)
Casing height incl. connection box in mm	4 1/8 (103)
Internal cutout dimensions in mm (width) with flush installation	1054
Internal cutout dimensions in mm (depth) with flush installation	518
Weight in lbs. (kg)	52 (24)
External cutout dimensions in mm (width) with flush installation	1078
External cutout dimensions in mm (depth) with flush installation	542
Total connected load in kW	11.20
Power cord length in in. (m)	3 (1.2)
Voltage in V	208-240
Frequency in Hz	50-60
<b>Standard accessories</b>	
Power cord	Yes

