86103 86104 INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions as you may need them a later date.

CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor.

Turn off the main power at the circuit breaker before installing the fixture in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustration.

ASSEMBLY AND INSTALLATION

- 1. Carefully push fixture wires through 6 inch stem (15). Thread 6 inch stem (15) onto top of fixture body (16). Push fixture wires from top of 6 inch stem (15) through 12 inch stem(14). Thread 12 inch stem (14) onto top of 6 inch stem (15) . Push fixture wires from top of 12 inch stem (14) through 18 inch stem (13), Thread 12 inch stem (14) onto top of 18 inch stem(13) . Determine desired hanging height of fixture. Select the stems to achieve that height. **Note: Pull fixture wires taut.**
- 2. Carefully pull house wires through center hole in mounting bracket (6). Secure mounting bracket (6) to outlet box(1) with outlet box screw (9).
- 3. Pull out the outlet wire and ground wire from the outlet box, make wire connections with wire nuts (5) as follows:
 - --Ribbed wire (w/o marking) or white wire from fixture to the white wire(2) from power source.
 - --Smooth wire (w/ marking) or black wire from fixture to the black wire(3) from power source.
 - --Ground wires from fixture to power source and tie to mounting bracket (6) with a ground screw (8).
- 4. Carefully raise fixture up to ceiling. Place canopy(10) of fixture over mounting bracket (6). Pass fixture mounting screws (7) through the holes on canopy(10) and Secure it with ball nuts (11).
- 5. Thread the stem with fixture to the loop(12).
- 6. Screw recommended bulb (E26 Edison/A19 bulb type, not included) into socket. Verify correct bulb wattage marked on socket of fixture. WARNING: DO NOT exceed maximum bulb wattage 7.Turn on the power

