

# 98101

## INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions, as you may need them at a later date.

### CAUTION

**WARNING:** Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor.

Turn off the main power at the circuit breaker before installing the fixture in order to prevent possible shock.

### GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustration.

### ASSEMBLY AND INSTALLATION

1. Pass fixture wire carefully through metal part(19).Connect the stems (18) (17)(16) (depending on desired height). Attach them to the all thread on the top of the fixture body (20), then thread the loop(15) into the stems (18/17/16).Pass wires carefully.
2. Attach mounting bar (6) with threaded nipple (10) and ceiling loop (12) and lock collar (13) to outlet box (1) secured with two box screws (8) .Secure the canopy (11) with lock collar (13) to the ceiling loop (12).
3. Open the quick link (14) then hook onto loop (15) and the ceiling loop (12).Then close the quick link(14).Slide the lock collar (13) and the canopy (11) to rest at the loop(15). Weave the fixture wires through the canopy(11), ceiling loop(12), and thread nipple (10) assembly.
4. Pull out the outlet wire and ground wire from the outlet box(1). Make wire connections with wire nut (5).
  - Ribbed wire (w/o marking) or white wire from light to White wire (3) from power source.
  - Smooth wire (w marking) or black wire from light to Black wire (2) from power source.
  - Tie the ground wire from fixture and from outlet box(1) to the ground screw(7) on the mounting plate(6).
5. Attach the fixture canopy(11) to the outlet box (1), secure it with lock collar (13).
6. Remove the socket ring (24) from the socket (21) of the fixture. Place the glass shade (22) and metal cap (23) over the socket then secure with socket ring (24) .
7. Install bulbs: (bulbs not include).  
(Don't exceed the maximum capacity recommended on the socket ring).

**INSTALLATION IS NOW COMPLETED**

