

99201

INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions, as you may need them at a later date.

CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor.

Turn off the main power at the circuit breaker before installing the fixture in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustration.

ASSEMBLY AND INSTALLATION

1. Attach mounting bar (6) with threaded nipple (10) and screw collar loop (12) and lock ring (13) to outlet box (1) secured with two box screws (9). Secure the canopy (11) with lock ring (13) to the screw collar loop (12).
2. Attach quick links (14) to the screw collar loop (12) and the appropriate amount of chain (15) (Depending on desired height).
3. **Screw loop (16) onto all thread at the top of fixture (17).** Slide the lock ring (13) and the canopy (11) down the chain (15). Open the quick link (14) at the other end and then hook onto top loop of fixture (16), close the quick links.
4. Weave the fixture wires through chain (15) (skipping every other chain link), screw collar loop (12), canopy (11) and thread nipple (10) assembly.
5. Pull out the outlet wire and ground wire from the outlet box. Make wire connections with wire nut (5).
 - Ribbed wire (W/O marking) or white wire from light to White wire (3) from power source.
 - Smooth wire (W marking) or black wire from light to Black wire (2) from power source.
 - Tie the ground wire from fixture and from outlet box (1) to the ground screw (7) on the mounting bar (6).
6. Raise canopy (11) against ceiling and lock it in position by lock ring (13) onto the screw collar loop (12).
7. Install bulbs: (bulbs (19) not included).
(Don't exceed the maximum wattage recommended on the socket (18)).

INSTALLATION IS NOW COMPLETED

