

INSTALLATION INSTRUCTION

Item#1279 (New. 02/04/2012)

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

PREPARATION (Fig. 1)

1. Shut off the power at the fuse box or circuit breaker. If necessary, remove the old fixture including the mounting hardware.
2. Carefully remove the fixture from the carton and check that all parts are included as shown in the illustration.
3. Thread the screws (D) into the pre-drilled holes in the circular strap (B) spaced the same distance apart as the holes in the top plate of fixture body (F); then secure them with the hex nuts (N).
4. Attach the circular strap (B) to the junction box with the mounting screws (C) (Size: #8-32N*L0.5"). The side of the circular strap marked "GND" must face out.

CONNECTING THE WIRES (Fig. 2)

5. While holding the fixture body (F) towards the ceiling, connect the electrical wires as shown in Fig.2, making sure that all wire connectors are secured. If your outlet has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the circular strap using the green screw provided. After wires are connected, tuck them carefully into the ceiling junction box.

COMPLETING THE INSTALLATION

6. Place the fixture body (F) over both screws (D) and secure fixture body against ceiling with knurled knobs (E).
7. Install the light bulb(s) (not included) in accordance with fixtures specifications. **(DO NOT EXCEED THE MAXIMUM WATTAGE RATING!). (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!).**
8. Thread the pipe (G) onto the bottom end of fixture body (F), and secure it with hex nut (M); then thread circular nut (K) over the pipe (G) so that it protrudes through.
9. Slide the plastic washer (L) and glass shade (H) through the pipe (G).
10. While holding the glass shade (H) in place, slide the lock washer (I) onto the pipe (G) and secure it with the finial (J). **Note:** adjust the hex nut (M), circular nut (K) and finial (I) so that the sides of the glass shade (H) and finial (I) are aligned.

Your installation is now complete. Return the power to the junction box and test the fixture.

Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

