



sensible sophistication



Mirabelle Dual Mount Stainless Steel Sink Installation Instructions

CAREFULLY READ THESE INSTRUCTIONS BEFORE YOU BEGIN.

- **Metal edges may be sharp – use caution when handling.**
- **For Experienced and Professional Installation Only.**
- **Follow all local standards and codes.**
- **For solid surface countertop installations only.**
- **A custom sink base cabinet is required.**
- **Proper installation requires a coordinated effort including advanced dialog between the designer (or customer), the cabinet maker, the countertop fabricator and the sink installer during the design and installation phase.**
- **Recommends providing the cabinet maker with the actual sink to be installed prior to cabinet fabrication.**



sensible sophistication

Installation

Caution: Please read all instructions before beginning the installation.

1. BEFORE YOU BEGIN

- Please note that this sink can be installed for the under mount (option A) or topmount (option B). Read this instruction carefully and decide which option before you start the installation.

- Make sure you are in compliance with all local plumbing and building codes.

- Unpack the new sink and inspect it carefully for damage. Return the sink to its original packing carton to protect it until you are ready to begin the installation.

- Check the desired sink location for sufficient space between the sink and the backsplash and proper clearance under the countertop for the faucet supply lines, drain assembly and cabinet.

- We recommend that undercounter sink installations be performed by experienced and trained installers.

2. RECOMMENDED TOOLS AND MATERIALS

- Sealant Drill and 1/2" (or Larger) Drill Bit
- Pencil
- Tape Measure
- Putty Knife
- Saber Saw or Keyhole Saw
- Safety Glasses
- Scissors
- Gloves
- Template(Supplied)

CAUTION: HANDLE WITH CARE

Use gloves and handle sink edges carefully as metal surfaces can be sharp.



sensible sophistication

Option A under mount installation

INSTALLING YOUR NEW SINK

A template has been included to help you cut an accurate opening in the countertop. Cut out the template, position the template as desired, and trace it on the countertop.

Drill a clearance hole inside the cutout line.


Cut out the countertop opening by carefully following the line traced from the template. Contract your countertop distributor for the best

Method of cutting your specific type of countertop (granite, Laminate, etc).

Drill the required faucet holes and install the faucet according to the Manufacturer's instructions.

Determine placement of clip brackets as indicated by template. Pre-drill Holes according to method recommended for your countertop material.

NOTE: THIS TEMPLATE IS ONLY A GUKDE ACTUAL SINK SHOULD BE PRESENT TO ENSUE PERFECT CUT OUT. ILLUSTRATION BELOW IS OF A SAMPLE TEMPLATE EACH SINK MODEL IS SUPPLIED WITH A CUSTOMIZED TEMPLATE.



- Clean the underside of the countertop, making sure the surface is smooth and free of defect.
- Apply a bead of silicone sealant along edge on underside of countertop.
- Position and align sink over opening. Press sink on to silicone seal.
- Re-check alignment and tighten clip brackets.
- Wipe off any excess sealant immediately with a damp cloth it will be difficult to remove if allowed to dry. Apply additional sealant if necessary.
- Allow the sealant to cure before proceeding.
- Connect the supply lines to the faucet and complete the faucet installation, following the instructions packed with the faucet.
- Connect drain assembly hand tight to check alignment Secure joint for watertight assembly.
- Install the garbage disposal, if applicable.




sensible sophistication


Option B top mount installation

1. If you are installing a sink to a new


a. Place sink upside down in the desired Position and trace completely the outside rim Using a soft lead pencil.



b. Then remove sink from countertop and draw Cutout line 5/16" inside the original rim with 1- 1/2" radius at corners line.



2. Using a sabre saw, start cutting from the Drilled hole along the cutout line. Support Cutout until the cut is completed.




3. Apply caulking compound to the perimeter of The cutout opening.
4. Attached faucet and sink strainer as necessary. Follow installation instructions supplied with your faucet.

5. Insert clips into the channel. Locate 3 clips in front and back, and two clips to each side. Be sure to arrange the clips evening around the sink. Position the clip assembly parallel to the channel.

Sink Type	Clip Use
Single Bowl	2 each in the front and back: 2 on each side
Double Bowl	3each in the front and back: 2 on each side
Bar Sink	1 each in the front and back: 1 on each side

6. Place the sink carefully into the cutout opening and be sure it is properly seated. make sure sink rim is covered with caulking all around and press down firmly around the perimeter of the sink rim.



7. Rotate the clamp on the clip 90 degrees to the channel and tighten screw clockwise. from the center clip using a long screwdriver.

8. Tighten all clips evenly and do not over tighten as damage can result.

9. Install drain and water supply fittings as necessary. Wipe excess caulking compound and check carefully as some adjustments for positioning and tightness may be required.



sensible sophistication



sensible sophistication

Limited Lifetime Warranty Residential Stainless Steel Sinks

WARRANTY: Subject to the limitations expressed herein, Seller warrants to the original purchaser that stainless steel sinks manufactured by Seller shall be free from defects in design, material and workmanship under Normal Use for the lifetime of the sink ("Warranty Period"). This warranty is void for any damage caused by misuse, abuse, neglect, acts of God, or improper installation. For the purpose of this section, "Normal Use" means in strict accordance with the installation, operation and maintenance manual for residential applications only. The warranty for products not manufactured by Seller is provided by the original equipment manufacturer.

REMEDIES: Seller shall repair or replace, at its option, any non-conforming or otherwise defective product, upon receipt of notice from Buyer during the Warranty Period at no additional charge.

SELLER HEREBY DISCLAIMS ALL OTHER EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS OR FITNESS FOR A PARTICULAR PURPOSE.

LIMITATION OF LIABILITY: UNDER NO CIRCUMSTANCES SHALL EITHER PARTY BE LIABLE TO THE OTHER FOR INCIDENTAL, PUNITIVE, SPECIAL OR CONSEQUENTIAL DAMAGES OF ANY KIND. BUYER HEREBY ACKNOWLEDGES AND AGREES THAT UNDER NO CIRCUMSTANCES, AND IN NO EVENT, SHALL SELLER'S LIABILITY, IF ANY, EXCEED THE NET SALES PRICE OF THE DEFECTIVE PRODUCT(S) PURCHASED DURING THE PREVIOUS CONTRACT YEAR.

LABOR ALLOWANCE: Seller makes NO ADDITIONAL ALLOWANCE FOR THE LABOR OR EXPENSE OF REPAIRING OR REPLACING DEFECTIVE PRODUCTS OR WORKMANSHIP OR DAMAGE RESULTING FROM THE SAME.

RECOMMENDATIONS BY SELLER: Seller may assist Buyer in selection decisions by providing information regarding products that it manufactures and those manufactured by others. However, Buyer acknowledges that Buyer ultimately chooses the product's suitability for its particular use, as normally signified by the signature of Buyer's technical representative. Any recommendations made by Seller concerning the use, design, application or operation of the products shall not be construed as representations or warranties, expressed or implied. Failure by Seller to make recommendations or give advice to Buyer shall not impose any liability upon Seller.

EXCUSED PERFORMANCE: Seller will make a good faith effort to complete delivery of the products as indicated by Seller in writing, but Seller assumes no responsibility or liability and will accept no backcharge for loss or damage due to delay or inability to deliver, caused by acts of God, war, labor difficulties, accidents, inability to obtain materials, delays of carriers, contractors or suppliers or any other causes of any kind whatever beyond the control of Seller.

Mirabelle is a registered trademark of Ferguson Enterprises, Inc.

For more information on Mirabelle products, visit mirabelleproducts.com.