

FACT SHEET

DANZZARE™

GLAZED CERAMIC FLOOR

COLORS



ALMOND DZ01



KHAKI DZ02



BROWN DZ03



GRAY DZ04

SIZES

13 × 13 Field Tile

18 × 18 Field Tile

TRIM

3 × 13 Bullnose*

*Floor bullnose trim is intended to coordinate with floor field tile in the normal 90-degree installation position.

APPLICATIONS

APPLICATION	INTERIOR			EXTERIOR	
	Residential	Light Commercial	Commercial	Residential	Commercial
Floors/Patios	✓				
Walls/Backsplashes	✓	✓	✓	✓	✓
Countertops	✓	✓	✓	✓	✓
Pool Decking					
Pool Lining	✓	✓	✓	✓	✓

Suitable for exterior walls in non-freezing climates when proper installation methods are followed.

TEST RESULTS

	ASTM#	Results
Water Absorption	C373	3.0 - 4.0%
Breaking Strength	C648	> 250 lbs
Scratch Hardness	MOHS	7.0
Chemical Resistance	C650	Resistant
Dynamic C.O.F.	A137.1	< 0.42
Abrasion resistance	C1027	3

A DCOF value of ≥ 0.42 is the new standard for tiles specified for commercial application in standard A137.1–2012, Section 9.6. It replaces the SCOF value of ≥ 0.60 referenced in ASTM C1028. For more information on the correlation between the two values and about the DCOF AcuTest™, please visit <http://daltile.com/information/DCOF>.

MANUFACTURING LOCATION

Mexico/USA