


# PISCES

## FR-W2503-54L

54" Ceiling Fan

# MODERN FORMS SMART FANS



### PRODUCT DESCRIPTION

Embracing the art of light, the natural Spanish Alabaster diffuser at the center of Pisces shimmers and casts an entrancing celestial glow from the stone's unique, natural variegations. Its three-blade configuration has a 54-inch sweep and quiet DC motor to effectively cool your space. An integrated, dimmable LED module offers a range of illumination options. Select from two sophisticated finishes of Matte Black or Matte White, or choose Matte Black or Matte White accented by a Soft Brass ring. Pair Pisces with your smart home ecosystem via the Modern Forms app.

### FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC Motor
- Includes BT remote control
- Optional wall control for 3, 4-way control sold separately
- Compatible with Modern Forms app

### AIRFLOW/ENERGY EFFICIENCY

<b>Weighted-Average/High Airflow CFM:</b>	3606/5700
<b>Weighted-Average/High Energy Use (W):</b>	18/25
<b>Estimated Yearly Energy Cost (\$):</b>	5
<b>Weighted-Average/High Efficiency (CFM/W):</b>	209
<b>Max RPM:</b>	169

### ORDER NUMBER

Model	Trim	Blade
FR-W2503-54L	<b>MB</b> Matte Black	<b>MB</b> Matte Black
	<b>MW</b> Matte White	<b>MW</b> Matte White
	<b>SB</b> Satin Brass	<b>MB</b> Matte Black
	<b>SB</b> Satin Brass	<b>MW</b> Matte White

Example: **FR-W2503-54L-SB/MB**

- \*Results may vary based on application and surroundings.
- \*This fan comes uni-pack - blade select options are not available

### SPECIFICATIONS

<b>Construction:</b>	Aluminum, ABS
<b>Blade:</b>	16° Pitch, 54" sweep
<b>Downrod:</b>	.75"W x 6"H included
<b>Mounting Slope:</b>	Up to 30°
<b>Wire:</b>	80"
<b>Hanging Weight:</b>	10.8 lbs
<b>Total Power:</b>	41W
<b>Standards:</b>	UL/cUL Wet Location listed, Title 24 JA8-2016 Compliant, Title 20, Energy Star rated
<b>Motor Type:</b>	108 x 20 sensorless DC motor

### WIRELESS PERFORMANCE

<b>Wi-Fi Range:</b>	Up to 150 ft*
<b>Bluetooth Range:</b>	Up to 150 ft*

### LUMINAIRE PERFORMANCE

<b>Light Source:</b>	LED
<b>Light Wattage:</b>	16W
<b>Lumens/Delivered Lumens:</b>	1497 - 1606 (Based on CCT) / 630
<b>Dimming:</b>	Integrated
<b>CRI:</b>	90
<b>CCT Color Temperature:</b>	3000K (2700K/4000K/5000K) selectable
<b>Rated Life:</b>	50,000 hours

The Modern Forms app synchronizes seamlessly with smart home devices you already own








modernforms.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760

**OPTIONAL ACCESSORIES**

Bluetooth Wall Control		<b>F-WCBT</b>	<b>WT</b> White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.
Bluetooth Remote Control		<b>F-RCBT</b>	<b>WT</b> White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with Modern Forms Smart Fans. Includes easy-to-install wall cradle and batteries.
Downrod		<b>XF-12</b> 12IN <b>XF-18</b> 18IN <b>XF-24</b> 24IN <b>XF-36</b> 36IN <b>XF-48</b> 48IN <b>XF-60</b> 60IN <b>XF-72</b> 72IN		All our downrods are .75 (in) I.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
Downrod Couplers		<b>XF-I</b>		Connects two downrods together.
Sloped Ceiling Kit		<b>XF-SCK</b>		Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: Wall Control: **F-WCBT-WT**, Remote Control: **F-RCBT-WT**, Downrod: **XF-12-BZ**, Downrod Coupler: **XF-I-MB**, Sloped Ceiling Kit: **XF-SCK-MW**

**SUGGESTED DOWNROD HEIGHT USAGE**

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

**SLOPED CEILING DEGREE CONVERSION CHART**

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

**NOTE:** Recommended maximum downrod length of 72" with 80" lead wire