



Specifications

Buy it for looks. Buy it for life.®

DESCRIPTION

- Digital thermostatic valve design with integral checkstops and 1/2" push fit connections

OPERATION

- Temperature range adjustment from 60 degrees F to 120 degrees F (16 degrees C to 49 degrees C). Factory maximum setting is 115 degrees (46 degrees C)
- Must be used with interface TS3495 series
- Valve must be installed in an area that has an access panel

FLOW

- Designed to deliver 11.5 gpm at 45 psi unrestricted flow (43.5L/min)
- Minimum flow 2.4gpm (9.1 L/min)

Pressure Differential- psi (KPa)


Pressure	psi	10	20	40	45
	KPa	69	138	276	310
Flow	gpm	5.6	7.8	11.0	11.5
	L/min	21.2	29.5	41.6	43.5

STANDARDS

- Third party certified to meet ASME A112.18.1/CSA B-125.1, CSA B125.3, ASSE1070 and all applicable requirements referenced therein
- Third party certified to meet UL1951
- Third party certified to meet FCC part 15

WARRANTY

- 5 year warranty against leaks, drips and operation defects to the original consumer purchaser
- 1 year warranty if used in commercial installations



**ioDIGITAL™
Roman Tub Valve**
Model: S4994

