
Voss™ Technical Specification **Pivoting Paper Holder**


YB5108


Stock Numbers:

- YB5108BN Pivoting Paper Holder **Brushed Nickel Finish**
- YB5108CH Pivoting Paper Chrome Finish
- YB5108ORB Pivoting Paper Oil Rubbed Bronze Finish

Dimensions:







Materials:

Paper Holder is constructed of zinc.

Installation Instructions:

- 1. Position the mounting template on the wall in the desired location. Using a level, align the template and tape it to the wall.
- 2. Remove each mounting post from the body by loosening the set
- 3. Place each mounting post on the template with notch facing down.
- 4. Mark the 2 large hole locations of each mounting bracket.
- 5. Attach each mounting bracket to the wall, using the wall anchors provided.
- 6. Mount each base on the corresponding mounting bracket. Check and make sure that the base set screw hole(s) are facing down. Assemble a set screw to each base. Use the allen wrench included in hardware kit to tighten each set screw and secure the assembly to the mounting bracket(s).
- 7. Tighten all 4 screws. Do not over tighten.
- 8. Place each post over the mounting plate (set screw down). Pivoting post with bar to be on left side. Tighten both set screws.

Cleaning Instructions:

To preserve the fine finish of this product, clean only with a soft damp cloth. Dry well. Do not use commercial or abrasive cleaners.

Stock Number:	Paper Holder
By Creative Specialties	·



25300 AL MOEN DRIVE • NORTH OLMSTED. OH 44070 CORPORATE HEADQUARTERS: (800) 321-8809 • FAX: (800) 848-6636 INTERNATIONAL: (440) 962-2000 • FAX: (440) 962-2726 CUSTOMER SERVICE (USA): 800-882-0116 • FAX: (888) 379-2720 WWW.MOEN.COM

©Copyright Creative Specialties International

Voss™ Technical Specification

24" Towel Bar

YB5124


Stock Numbers:

- □ YB5124BN 24" Towel Bar Brushed Nickel Finish
- □ YB5124CH 24" Towel Bar Chrome Finish
- ☐ YB5124ORB 24" Towel Bar
 Oil Rubbed Bronze Finish

Dimensions:



LENGTH	18"	24"
DIM "A"	18.00"	24.00"
DIM "B"	2.11"	2.11"
DIM "C"	20.11"	26.11"
DIM "D"	2.92"	2.92"





Materials:

Towel Bar Posts are constructed of zinc and **towel bar** is constructed of stainless steel.

Installation Instructions:

- 1. Position the mounting template on the wall in the desired location. Using a level, align the template and tape it to the wall.
- 2. Remove each mounting post from the body by loosening the setscrew.
- 3. Place each mounting post on the template with notch facing down.
- 4. Mark the 2 large hole locations of each mounting bracket.
- 5. Attach each mounting bracket to the wall, using the wall anchors provided.
- 6. Mount each base on the corresponding mounting bracket. Check and make sure that the base set screw hole(s) are facing down. Assemble a set screw to each base. Use the allen wrench included in hardware kit to tighten each set screw and secure the assembly to the mounting bracket(s).
- 7. Tighten all 4 screws. Do not over tighten.
- 8. Place each post over the mounting plate (setscrew down). Pivoting post with bar to be on left side. Tighten both setscrews.

Cleaning Instructions:

To preserve the fine finish of this product, clean only with a soft damp cloth. Dry well. Do not use commercial or abrasive cleaners.

Stock Number:	24"	Towel Bar
By Creative Specialties		

25300 AL MOEN DRIVE • NORTH OLMSTED, OH 44070 CORPORATE HEADQUARTERS: (800) 321-8809 • FAX: (800) 848-6636 INTERNATIONAL: (440) 962-2000 • FAX: (440) 962-2726 CUSTOMER SERVICE (USA): 800-882-0116 • FAX: (888) 379-2720 WWW.MOEN.COM



Voss™ Technical Specification

18" Towel Bar

YB5118


Stock Numbers:

- □ YB5118BN 18" Towel Bar Brushed Nickel Finish
- □ YB5118CH 18" Towel Bar Chrome Finish
- □ YB5118ORB 18" Towel Bar Oil Rubbed Bronze Finish

Dimensions:



LEN	GTH	18"	24"
DIM	" A "	18.00"	24.00"
DIM	"B"	2.11"	2.11"
DIM	"C"	20.11"	26.11"
DIM	"D"	2.92"	2.92"





Materials:

Towel Bar Posts are constructed of zinc and **towel bar** is constructed of stainless steel.

Installation Instructions:

- 1. Position the mounting template on the wall in the desired location. Using a level, align the template and tape it to the wall.
- 2. Remove each mounting post from the body by loosening the setscrew.
- 3. Place each mounting post on the template with notch facing down.
- 4. Mark the 2 large hole locations of each mounting bracket.
- 5. Attach each mounting bracket to the wall, using the wall anchors provided.
- 6. Mount each base on the corresponding mounting bracket. Check and make sure that the base set screw hole(s) are facing down. Assemble a set screw to each base. Use the allen wrench included in hardware kit to tighten each set screw and secure the assembly to the mounting bracket(s).
- 7. Tighten all 4 screws. Do not over tighten.
- 8. Place each post over the mounting plate (setscrew down). Pivoting post with bar to be on left side. Tighten both setscrews.

Cleaning Instructions:

To preserve the fine finish of this product, clean only with a soft damp cloth. Dry well. Do not use commercial or abrasive cleaners.

Stock Number:	18"	Towel Bar
By Creative Specialties	_	

25300 AL MOEN DRIVE • NORTH OLMSTED, OH 44070 CORPORATE HEADQUARTERS: (800) 321-8809 • FAX: (800) 848-6636 INTERNATIONAL: (440) 962-2000 • FAX: (440) 962-2726 CUSTOMER SERVICE (USA): 800-882-0116 • FAX: (888) 379-2720 WWW.MOEN.COM

©Copyright Creative Specialties International



Voss™ Technical Specification Decorative Tank Lever


Stock Numbers:


- YB5101BN Decorative Tank Lever **Brushed Nickel Finish**
- YB5101CH Decorative Tank Lever Chrome Finish
- YB51010RB Decorative **Tank Lever** Oil Rubbed Bronze Finish

Materials:

Tank Levers are constructed of zinc.

Dimensions:





Installation Instructions:

- Remove existing tank lever.
- Remove the arm mechanism from the new tank lever by loosening nut.
- Unscrew the tank nut. The thread for the tank nut is a left handed thread.
- Position the new tank lever through the tank hole. The tank lever handle should be pointing away from the toilet bow I.
- Tighten nut. Depending on the curvature of the tank, there might be a slight hap between the outside of the tank and the base of the lever.
- 6. Place the arm mechanism of the tank lever post. Adjust the arm up or down as needed. Tighten nut to secure the arm in place.
- 7. Adjust the arm mechanism from side to side as needed. Make sure the arm does not come into contact with the tank wall or the flush mechanism. Tighten screw (A) to lock the arm in place.
- Attach the flapper valve chain to one of the provided slots on the arm. Be sure to eliminate any slack in the chain.
- Make sure no water is leaking through the flapper when the handle is in its normal position (not flushing). If it is, adjust the arm as needed.

Cleaning Instructions:

To preserve the fine finish of this product, clean only with a soft damp cloth. Dry well. Do not use commercial or abrasive cleaners.

Stock Number:	Tank Lever
By Creative Specialties	

25300 AL MOEN DRIVE • NORTH OLMSTED. OH 44070 CORPORATE HEADQUARTERS: (800) 321-8809 • FAX: (800) 848-6636 INTERNATIONAL: (440) 962-2000 • FAX: (440) 962-2726 CUSTOMER SERVICE (USA): 800-882-0116 • FAX: (888) 379-2720 WWW.MOEN.COM

©Copyright Creative Specialties International

Literature #BA1618