



EQ701 Prague



EQ712 Rhodes

PRAGUE AND RHODES

Prague is created from short, fragmented lines giving an overall subtle, geometric feel. Rhodes complements it by adding a layer of intersecting lines. Both patterns allow for expressive design ideas and long-lasting durability in any commercial interior.

PRAGUE

Product Type	Carpet Tile
Construction	Tufted
Surface Appearance	Textured Patterned Loop
Gauge	1/12" (47.00 rows per 10 cm)
Tufted Weight	16 oz/yd ² (542 g/m ²)
Pile Thickness	.103" (2.62 mm)
Stitches Per Inch	12.5 (49.21 per 10 cm)
Density	7,296
Weight Density	110,899
Dye Method	100% Solution Dyed
Fiber Type	Colorstrand® SD Nylon
Stain Release Technology	Mohawk Protection Plus Stain
Soil Release Technology	Mohawk Protection Plus Soil
Primary Backing	Non-Woven Synthetic
Secondary Backing	UltraSet®
Recycled Content	Contains a minimum of 39% pre-consumer recycled content by total product weight
NSF 140	Gold
Installation Method	Quarter Turn / Brick Ashlar / Vertical Ashlar / Monolithic / Multi Directional
Pattern Repeat	N/A
Indoor Air Quality	Green Label Plus Certified # 1098
Size/Width	24" x 24" (.6096 m x .6096 m)
Flammability	ASTM E 648 Class 1 (Glue down)
Smoke Density	ASTM 662 Less than 450
Static Propensity	AATCC-134 Under 3.5 KV
Appearance Retention Rating (TARR)	Heavy Traffic
Warranties	Lifetime Limited Wear Warranty Lifetime Limited Edge Ravel, Zippering, Delamination and Dimensional Stability Warranty Lifetime Limited Static Protection Warranty Lifetime Limited Colorfastness to Light Warranty 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Atmospheric Contaminants

RHODES

Product Type	Carpet Tile
Construction	Tufted
Surface Appearance	Textured Patterned Loop
Gauge	1/12" (47.00 rows per 10 cm)
Tufted Weight	16 oz/yd ² (542 g/m ²)
Pile Thickness	.118" (3.00 mm)
Stitches Per Inch	12.5 (49.21 per 10 cm)
Density	6,592
Weight Density	100,198
Dye Method	100% Solution Dyed
Fiber Type	Colorstrand® SD Nylon
Stain Release Technology	Mohawk Protection Plus Stain
Soil Release Technology	Mohawk Protection Plus Soil
Primary Backing	Non-Woven Synthetic
Secondary Backing	UltraSet®
Recycled Content	Contains a minimum of 39% pre-consumer recycled content by total product weight
NSF 140	Gold
Installation Method	Quarter Turn / Brick Ashlar / Vertical Ashlar / Monolithic / Multi Directional
Pattern Repeat	N/A
Indoor Air Quality	Green Label Plus Certified # 1098
Size/Width	24" x 24" (.6096 m x .6096 m)
Flammability	ASTM E 648 Class 1 (Glue Down)
Smoke Density	ASTM 662 Less than 450
Static Propensity	AATCC-134 Under 3.5 KV
Appearance Retention Rating (TARR)	Heavy Traffic
Warranties	Lifetime Limited Wear Warranty Lifetime Limited Edge Ravel, Zippering, Delamination and Dimensional Stability Warranty Lifetime Limited Static Protection Warranty Lifetime Limited Colorfastness to Light Warranty 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Atmospheric Contaminants

Cover: Prague Carpet Tile 589 Designing Point and Rhodes Carpet Tile 589 Designing Point

Prague



521 Visual Edge 589 Designing Point 841 Defined Sculpture 858 Individual Twist 869 Functional Space 878 Rethinking Form 979 Structural Form

Rhodes



521 Visual Edge 589 Designing Point 841 Defined Sculpture 858 Individual Twist 869 Functional Space 878 Rethinking Form 979 Structural Interest



Up to 2,000 sq. yds. available within 10 business days or less

